UTRGV Procurement Management UNIVERSITY OF TEXAS RIO GRANDE VALLEY

1201 West University Drive · Edinburg, Texas 78539-2999 · Office: (956) 665-7021 · Fax: (956)665-2164 · Email: purch@utrgv.edu

DATE: February 4, 2019

MEMORANDUM

TO: All Interested Bidders

FROM: Marilu Reyes Senior Procurement Specialist

SUBJECT: REQUEST FOR PROPOSAL (RFP) No: 19-MG-01

ADDENDUM NUMBER TWO

- 1. Architect Updates to Bid Documents See Architect Addendum # 4
- 2. Deadline for Questions February 5, 2019 at 12:00 pm CST.

Except for the items, listed, above all other items shall remain the same and unchanged **Please sign below to acknowledge receipt of addendum and return with your proposal.**

Sincerely,

The University of Texas Rio Grande Valley

Company Name

Authorized Signature

Date



3301 N. McColl Rd. McAllen, Texas 78501



University of Texas Rio Grande Valley

School of Medicine Jackson Road Remodel

UTRGV PROJECT NUMBER #PED-18-33 Edinburg, Texas Boultinghouse Simpson Gates Project No. 1802

Addendum #4 (Bid Package #2) to the drawings and specifications dated October 31st, 2018 for the UTRGV SOM Jackson Road Remodel.

This addendum shall become part of the bidding and contract documents, and shall amend, modify and supersede the original documents. Acknowledge receipt of this Addendum in the space provided on the Bid Form. Failure to do so may subject the Bidder to disqualification.

Item

Description

General:

- **4-1** Add **Spectrum Lighting, Inc. San Antonio** to the list of approved vendors for the lighting package.
- 4-2 Add Mannington to the list of approved vendors for the carpet and LVT flooring.

Architectural:

- **4-3** Replace VCT flooring with carpet flooring as per the attachment ADD4-1.
- **4-4** See attachment ADD4-2 and ADD4-3 for enlarged floor plans showing interior architectural millwork that was deleted from the interior furniture package and will now be part of the architectural millwork of bid package #2.
- **4-5** See attachments ADD4-4, ADD4-5, ADD4-6, ADD4-7, ADD4-8, ADD4-9, ADD4-10, ADD4-11, ADD4-12, ADD4-13, ADD4-14, ADD4-15, ADD4-16, ADD4-21 for new interior elevations showing new architectural millwork to be added to the project.
- **4-6** See attachments ADD4-17, ADD4-18, ADD4-19 and ADD4-20 for new architectural millwork section details that correspond to the new interior elevation markers on the enlarged plans attachments ADD4-2 and ADD4-3.

Mechanical Electrical Plumbing:

4-7 See attached MEP Addendum provided by Ethos Engineering.

END OF UTRGV SOM Jackson Road Remodel ADDENDUM #4

















FACILITIES PLANNING & CONSTRUCTION 956.665.2770

3804 S. JACKSON RD. | EDINBURG, TX | 78539

 \mathbb{A}





















RioGrande Valley

Boultinghouse Simpson Gates

Project # 1802 UTRGV PROJECT # PED-18-33 UTRGV - SCHOOL OF MEDICINE - JACKSON RD.

3804 S. JACKSON RD. | EDINBURG, TX | 78539

4 FEBRUARY 20

ue Date - 2-4-2019 \mathbb{A}

OVEMBER 2018 MILLWORK ELEVATION

ADD4-16

FACILITIES PLANNING & CONSTRUCTION 956.065.2770











Boultinghouse Simpson Gates Project # 1802 UTRGV PROJECT # PED-18-33 UTRGV - SCHOOL OF MEDICINE - JACKSON RD. 3804 S. JACKSON RD. | EDINBURG, TX | 78539

4 FEBRUARY 20

ue Date - 2-4-2019 \mathbb{A}

NOVEMBER 2018 MILLWORK ELEVATION

ADD4-21

RioGrande Valley

FACILITIES PLANNING & CONSTRUCTION 956.065.2770



119 W. Van Buren Ave. Ste. 101 Harlingen, TX 78550 Off: (956) 230-3435 Fax: (956) 720-0830 www.ethoseng.net

February 4, 2019 UTRGV School of Medicine Jackson Rd.





A. PURPOSE AND INTENT

This addendum is issued for the purpose of modifying the plans and specifications for the project referenced above.

This addendum shall become part of the contract and all contractors shall be bound by its content. All aspects of the specifications and drawings not covered herein shall remain the same.

The General Conditions and the Special Conditions of the specifications shall govern all parts of the work and apply in full force to this addendum.

B. SCOPE

I. DRAWINGS:

- 1. Sheet MEP1.01:
 - a. Electrical Keyed Note #6:
 - Provide an allowance of \$15,000 for electric utility pad mount transformer installation. Also included in this allowance amount is a new concrete pad in the event that the existing does not meet the approval of the utility company. Coordinate with utility company. See attached AEP concrete pad requirements.
 - b. Electrical Keyed Note #8:
 - i. Apply key note as illustrated below.



- c. Fire Suppression : Refer to attached revised full size sheet.
- 2. Sheet M3.01:
 - a. Mechanical Keyed Note #8:
 - i. Key note will not be used. Fire dampers are not required.
- 3. Sheet M3.02:
 - a. Mechanical Keyed Note #8:
 - i. Key note will not be used. Fire dampers are not required.
- 4. Sheet M5.01:
 - a. ROOF MOUNTED DEDICATED OUTSIDE AIR UNIT SCHEDULE: replace schedule in its entirety. See attached new schedule sheet.
 - b. ROOFTOP UNIT SCHEDULE: replace schedule in its entirety. See attached new schedule.
 - c. Clarification: Windstorm certification is not required for this project. However, the contractor shall ensure that installations of curbs and RTUs are capable of withstanding the local wind pressures. It is our understanding that Owner is pre-purchasing the RTUs with the engineered/curbs. The curbs are being engineered/designed by the RTU manufacturer. Owner and RTU manufacturer shall provide the installation instructions of the curbs, RTUs and related attachments and contractor shall follow those instructions. Contractor shall coordinate with Owner and RTU manufacturer to ensure all information is provided.









NOTES:

- 1. Instrument Transformers (CTS) are furnished and installed by Company prior to connection of customer service cables.
- Customer shall provide NEMA type Terminal Lugs for customer owned service conductors where required. Power company to secure cable terminations. Stacking lugs may be required to accomodate the number of service conductors per transformer bushing.
- 3. This standard application for a single customer Three Phase Pad-Mounted Transformer.
- 4. Customer provides Meter Socket to be installed by customer or contractor in a Plumb Position at location, using removable corrosion resistant fasteners. All Meter Sockets installed in the Complany's service territory shall be of a type approved by the company and meet all requirements in construction and features. In addition, Meter Sockets purchased by the Customer shall be UL listed and labeled in accordance with National Electric Code.
- 5. Transformer Pad location and the location of conduits for Conductor/Meter Control Cable to be specified by AEP. The Meter location is to be within 25 feet of the Transformer Pad location. When the building is located at a distance greater then 25 feet from the Transformer Pad location, the Meter is to be mounted on a support structure at a location where the distance from the Transformer Pad location is not greater than 25 feet. For free standard Metering
- 6. The Meter Socket shall be grounded. The Meter Socket shall be bonded through a separate equipment-Grounding Conductor connected to the grounded service conductor (usually the neutral). In some jurisdictions the grounding of the Meter Socket will be supplemented with the use of a driven Ground Rod in addition to bonding to the Grounded Service Conductor.
- 7. Schedule 80 Rigid Conduit required for driveways and parking lots.

ALE TEXAS

| Three Phase Pa | d-Mounted Trans | former & M | etering Installation |
|------------------|-----------------------------|----------------|----------------------|
| Date: 04/30/2012 | Revised Date: 10/02/2013 | Scale: None | Page 5 of 7 |







SCALE :NONE

PROVIDE FREE STANDING FIRE DEPARTMENT CONNECTION. REFER TO DETAIL ON THIS SHEET.

PROVIDE 4" FIRE SPRINKLER LINE TO SERVE FREE STANDING FDC OUTSIDE THE BUILDING. VERIFY SIZE BY MEANS OF CALCULATION AND COORDINATE WITH GENERAL CONTRACTOR. REFER TO ARCHITECTURAL DRAWINGS FOR DEMOLITION AND REPAIR DETAILS OF EXISTING ASPHALT.

EXISTING FIRE HYDRANT AT THIS APPROXIMATE LOCATION.

(5.)

 $\langle 6. \rangle$

GENERAL NOTES:

- COORDINATE WORK AMONG ALL DISCIPLINES. IT IS NOT THE INTENT OF THESE DOCUMENTS TO DICTATE WHO MUST DO THE WORK. ALL WORK SHOWN IS THE RESPONSIBILITY OF THE (PRIME) CONTRACTOR.
- FIELD VERIFY PROJECT SITE EXISTING CONDITIONS AND ELEVATIONS PRIOR TO 2. BEGINNING ANY WORK.
- COORDINATE ELECTRICAL AND PLUMBING WITH GENERAL CONSTRUCTION. 3.
- PHASING AND SEQUENCE OF CONSTRUCTION SHALL BE PER ARCHITECTURAL DRAWINGS AND SPECIFICATIONS.
- FIELD VERIFY/SPOT EXACT LOCATIONS AND EXISTING CONDITIONS OF EXISTING PLUMBING, AND ELECTRICAL. IT IS THE INTENT OF THESE PLANS TO PROVIDE A COMPLETE AND WORKABLE SYSTEMS. SHOULD BIDDER FIND OMISSIONS OR DISCREPANCIES IN THE PLANS, BIDDER SHALL NOTIFY THE ENGINEER PRIOR TO THE BID DATE AND A WRITTEN CLARIFICATION WILL BE ISSUED.
- DAMAGED ITEMS SHALL BE REPAIRED AT NO ADDITIONAL COST TO OWNER. 6. CONTRACTORS ARE REQUIRED TO SEARCH AND INVESTIGATE FOR EXISTING UTILITIES BEFORE EXCAVATING.
- ALL MATERIALS AND LABOR, WHETHER SPECIFICALLY INDICATED ON PLANS OR 7. NOT, WHICH ARE NECESSARY FOR THE PROPER INSTALLATION AND FUNCTION OF THE SYSTEM SHALL BE FURNISHED BY THIS CONTRACTOR. INCLUDE ALL COSTS OF CHANGES, IF/AS REQUIRED IN BID PROPOSAL.
- PROVIDE J-BOXES (POLYMER CONCRETE) AS REQUIRED FOR PULL WIRING. 8.
- ELECTRICAL WIRING SHALL NOT BE SPLICED BELOW GRADE. 9.
- PERFORM ALL WORK PER LATEST VERSION OF NATIONAL ELECTRICAL CODE, AND 10. APPLICABLE LOCAL CODES AND ORDINANCES, UNLESS DRAWINGS OR SPECIFICATIONS HAVE MORE STRINGENT REQUIREMENTS.
- CONTRACTOR IS RESPONSIBLE FOR ALL PERMITS AND FEES ASSOCIATED WITH 11. PROJECT, INCLUDING FEES FOR INSPECTIONS, APPLICATIONS, AND PROVISION OF NEW SERVICES.
- CONTRACTOR WHO WILL ACTUALLY PERFORM WORK MUST APPLY FOR ALL 12. REQUIRED PERMITS.
- NOTIFY ENGINEER OF ANY ASPECTS OF DESIGN WHICH ARE THOUGHT TO BE IN 13. NONCOMPLIANCE WITH APPLICABLE CODES.
- COORDINATE ALL WORK WITH OTHER TRADES; COORDINATE SCHEDULE OF 14. WORK WITH ALL SUB-CONTRACTORS TO ACHIEVE SMOOTH FLOW OF CONSTRUCTION.
- SEAL AROUND ELECTRICAL RACEWAYS AT ALL WALLS, A/C ROOMS AND WALL 15. LOUVER PENETRATIONS WITH FIREPROOF CAULKING. RE: SPECS. PROVIDE FLASHING AROUND PENETRATION, BOTH INSIDE AND OUTSIDE, TO PROVIDE FINISHED LOOK.
- TIME OR MONEY ALLOWANCES WILL NOT BE MADE TO ACCOMMODATE UTILITY CONFLICTS THAT CAN BE REASONABLY RESOLVED BY COORDINATION DURING SHOP DRAWING PHASE.
- 17. CONTRACTOR SHALL REVIEW COMPLETE DOCUMENTS PRIOR TO SUBMITTAL OF PROPOSAL TO GAIN COMPLETE UNDERSTANDING OF PROJECT SCOPE, WORK BY OTHERS, AND ELECTRICAL WORK ASSOCIATED WITH OTHER DISCIPLINES.
- 18. MAINTAIN MANUFACTURER RECOMMENDED CLEARANCE AROUND ALL EQUIPMENT.
- AFFIX ID TAGS TO ALL DIVISION 26 EQUIPMENT. 19.
- CONTRACTOR IS RESPONSIBLE FOR COORDINATION WITH MECHANICAL AND 20. PLUMBING CONTRACTOR REGARDING EQUIPMENT SIZES AND TYPES OF ELECTRICAL INTERFACE EQUIPMENT REQUIRED.
- 21. FIELD VERIFY ALL CONDITIONS AND MEASURE DIMENSIONS WITHIN THE BUILDING PRIOR TO ORDERING EQUIPMENT AND/OR PROCEEDING WITH INSTALLATION.
- ALL EQUIPMENT SHALL BE FACTORY TESTED, AND CONTRACTOR SHALL VERIFY 22. THEIR CONDITION PRIOR TO INSTALLATION. CONTRACTOR IS RESPONSIBLE FOR EQUIPMENT DAMAGED DURING MOVING AND INSTALLATION.
- EQUIPMENT FOUND DEFECTIVE PRIOR TO FINAL ACCEPTANCE SHALL BE 23. REPLACED AT NO COST TO OWNER.
- WORK TO BE DONE UNDER ALLOWANCES BECOMES AN INTEGRAL PART OF THE 24. PROJECT AND RESPONSIBILITY OF CONTRACTOR ONCE ALLOWANCE IS APPROVED.
- SLEEVE ALL EXTERIOR WALL PENETRATIONS. 25.
- CONTRACTOR SHALL NOT PROCEED WITH ANY WORK INVOLVING A CHANGE IN 26. PROJECT SCOPE OR COST WITHOUT FIRST HAVING OBTAINED ENGINEER'S APPROVAL IN WRITING. UNLESS ENGINEER HAS AGREED TO SUCH CHANGE PRIOR TO IT BEING DONE, AND HAS AGREED THAT AN INCREASE IN COST ASSOCIATED WITH SUCH CHANGE IS WARRANTED; CONTRACTOR WILL NOT BE REIMBURSED FOR SUCH CHANGE.

ELECTRICAL KEYED NOTES:

- 1 EXISTING ELECTRIC UTILITY 3 PHASE OVERHEAD SERVICE LINES. 2 EXISTING ELECTRIC UTILITY POWER POLE. 3 NEW OVERHEAD UTILITY POWER LINE.
- 4 NEW ELECTRIC UTILITY POWER POLE WITH RISER DIP POLE.
- PROVIDE NEW UNDERGROUND PRIMARY ELECTRIC CONDUITS WITH 2" RED CONCRETE. RE-USE PORTION OF EXISTING. SEE RISER DIAGRAM.
- 6 PROVIDE NEW ELECTRIC UTILITY PAD MOUNT TRANSFORMER ON EXISTING CONCRETE PAD.
- 7 PROVIDE NEW UNDERGROUND SECONDARY FEEDERS IN EXISTING RACEWAYS.
- 8 PROVIDE NEW ELECTRIC UTILITY SERVICE METER ON FREE STANDING RACK.
- 9 EXISTING BUILDING MAIN SWITCH DISCONNECT.
- 10 PROVIDE NEW POLE LIGHTS. SWITCH EXTERIOR POLE LIGHTS THROUGH RELAY PANEL. BRANCH CIRCUIT: 1" - 2#8 & #10G. SEE CORRESPONDING PANEL SCHEDULE.
- [11] CONNECT IRRIGATION CONTROLLER.







119 W. VAN BUREN AVE. STE. 101 PHONE: 956-230-3435 **TEXAS REGISTERED** ENGINEERING FIRM F-15998

| Project # 18v15 Project # 18v15 Owner UTRGV - SCHOOL OF MEDICINE - JACKSON RD. | School of Medicine | 494 F: 956.630.2058 9 5 6 . 6 6 5 . 2770 |
|--|--|---|
| Project # 18v15 Owner UTRGV - SCHOOL OF MEDICINE - JACKSON RD. Enter address here Finer address here | Boultinghouse Simpson | A RCHITECTS 3301 N. McCOLL RD McALLEN, TX 78501 P: 956.630.9 |
| | Project # 18v15 Owner UTRGV - SCHOOL OF MEDICINE - JACKSON RD. | Enter address here |

| | 0.A./ | | | | | | | | | ΓΙΟΝ | | | | DEHUMI | DIFICATION | CONDIT | ON |
|-------------------|--|---|---|---|--|--|--|---|--|---|---|--|--|--|--|--|---|
| MARK | SUPPLY AIR CFM | SERVING | ESP (in. water | ELE V-PH | CT. MCA | MOCI | P BLOWER HP | EAT (DB/WB) | LAT (DB/WB) | AIR (CON | DN TCAP D. MBH | SCAP MBH | (D | EAT 9B/WB) | LAT (DB/WB) | AIF) CC | r on)nd. |
| OAS-1 | 1,800 | RTUS-1, 2 | 0.50 | 208-3 | 3-60 68.80 | 90.00 |) 2.30 | 100.4/76.5 | 51.0/51.0 | 105 | 5 153.70 | 97.30 | 83 | 3.3/79.4 | 52.8/52.8 | 3 | 95 |
| OAS-2 | 1,800 | RTUS-2, 3, 4 | 0.50 | 208-3 | 3-60 68.80 | 90.00 |) 2.30 | 100.4/76.5 | 51.0/51.0 | 105 | 5 153.70 | 97.30 | 83 | 3.3/79.4 | 52.8/52.8 | 3 | 95 |
| 0TES: 1. 2 | | | ACKAGED UNITS | | | | DENSERS DESIG | GNED FOR 100% | | | ON. | | | | | | |
| 2. 3. 4. | PROVIDE MI PROVIDE MI | NIMUM OF ONE IN | VERTER COMP | RESSOR FOR | R FULL MODULA | ATION OF R COIL. | CAPACITY ANI | D ACCURATE LEA | VING AIR TEM | ERATUF | RE CONTROL. | | | | | | |
| 5. 6. | PROVIDE GA | ALVANIZED FILTER ABINET WITH 1" R- | R FRAMES AND 3 7 (3-15 TONS) OF | 04 STAINLE R 2" R-13 (16 | SS STEEL DRAII + TONS) DOUBL | N PANS. E WALL | CONSTRUCTIO | N WITH FOAM IN | SULATION. | | | | | | | | |
| 7. 8. | FURNISH DIF E-COATED E | RECT DRIVE EVAP EVAPORATOR, RE | PORATOR FAN, A HEAT, AND CON | ND ECM MC DENSER CO | TOR OR VFD A | ND NON- STM B11 | OVERLOADING 7-90, ASTM D224 | MOTORS. PROV 47-92, AND ASTM | IDE TOTALLY E 0870-92 FOR 6, | NCLOSE)00 HRS | D FAN MOTOR SALT SPRAY, 1 | S. ,000 HRS | S HUMIDI | ITY IMMER | SION RESI | STANCE, | AND 2 |
| 9. | APPROVED PERFORMAN | MFRS THAT DO N NCE PENALTY OF | OT MEET SPECIE \$14/TON FOR EV | IED EFFICIE ERY 1/10 OF | NCIES SHALL II | NCLUDE ER THAN | A PERFORMAN | CE PENALTY, PA EER BASED ON A | D TO OWNER. STANDARD UN | IT OF TH | E SAME CAPA | CITY AT A | AHRI CON | NDITIONS. | | | |
| 10. 11. | UNITS SHAL | L BE RATED IN AC CTLY EXTERNAL \$ | CORDANCE TO STATIC PRESSUR | AHRI 340/ 36 Re and IS IN | 0. Addition to A | ANY FILT | ERS, COILS OR | OTHER ACCESS | ORIES INCLUDE | D WITH | THE MAU | | | | | | |
| 12. 13. | PROVIDE SIN | NGLE POINT OF E | LECTRICAL. SAF TROL TO 35F. | | | ED BY DI | V. 26. COORDIN | ATE WITH ELECT | RICAL CONTRA | CTOR. | | | | | | | |
| 14. | PROVIDE FA 1) 100% OUT | CTORY INSTALLE | ED UNITARY CON OL | | APABLE OF | | | | | | | | | | | | |
| | 2) CONSTAN 3) BACNET II | IT VOLUME SUPPI NTERFACE | LY AIR FLOW CO | NTROL. | | | | | | | | | | | | | |
| 15. | 4) MODULAT | C 2012 COMPLIAN | IUMIDIFICATION | CONTROL ACHMENTS | FROM UNIT TO |) CURB A | ND CURB TO S | TRUCTURE. EQU | PMENT OR CU | RB MANU | JFACTURER IS | RESPON | ISIBLE F | OR PROVI | IDING ENGI | NEERED | DETAI |
| | 2) CURB TO | STRUCTURE. | | | | | | | | | | | | | | | |
| | 3) CURB AND REFER TO A | | AND STRUCTURA | NGTH. L DRAWING | | UBSTRA | TE DETAILS. | | | | | | | | | | |
| | EQUIPMENT BOTH, THE E | OR CURB MANU | ACTURER IS AL | SO RESPON | SIBLE FOR PRO | N DRAW | ENGINEERED IN | PERFORMED SP | AWINGS FOR II ECIFICALLY FC | EMS 1 A R THIS B | ND 2 LISTED AI BUILDING AND F | BOVE. PROJECT | SITE AN | ND STAMP | PED AND SE | EALED BY | A TE |
| 16. 17. | PROVIDE CC | S WILL NOT BE AP OMBO 2"/4" FILTEF | RACK INTERAL | TO THE UNI | T WITH ONE SE | ED ABOV T OF 2" (| GALVANIZED FIL | TER FRAMES WI | TH MERV 8 FIL | ERS AN | D ONE SET OF | 4" MERV | 14 FILTE | ERS. ADD | 0.75" PRES | SURE DF | rop f |
| 18. | PROVIDE IN | TERIOR COATING | RATED AT 10,00 | UHR ASTM B | 5117. | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | |
| ROOI | FTOP U | INIT SCHE | EDULE | | | | | | | | | | | | | | |
| | | NOMINAL | SUPPLY | OA | | ESP | MIN. | FLA MCA | MOCP | ELECT. | AIR ON | тс | DTAL | COOL SENS | LING | EAT | |
| M/ R1 | ARK TU-1 | 10 | 5000 | CFM 1030 | FROM (DOAS-1 | (INCHES) 1.5 | HP 8 | A A 49.4 49.4 | A 60 | V-PH-HZ 208-3-60 | COND. | B ⁻ | TUH 16.5 | BTL 106 | JH 5.1 | DB/WB 75.0/63. | 0 |
| R | TU-2 | 7 | 3350 | 770 | DOAS-1 | 1.5 | 4 | 41.4 36.3 | 45 | 208-3-60 | 100 | 8 | 37.1 | 75. | .8 | 75.0/63. | 0 |
| D | TII2 | 10 | 4200 | 725 | DUVE 3 | 15 | 1 | 101 117 | 60 | 208 3 60 | 100 | 1. | 127 | 05 | Q | 75 0/63 | |
| R1 R1 | TU-3 TU-4 | 10 5 | 4200 2315 | 725 550 | DOAS-2 DOAS-2 | 1.5 1.5 | 4 | 49.4 44.7 27.1 27.1 20.2 20.2 | 60 35 | 208-3-60 208-3-60 | 100 100 | 1 ⁻ 5 | 13.7 6.5 | 95. 50. | .8 | 75.0/63. 75.0/63. | 0 |
| R1 R1 DTES: | TU-3 TU-4 TU-5 1. 2. 3. 4. 5. 6. 7. 8. 9 | 10 5 7 PROVIDE ROOF O PROVIDE CABINE PROVIDE HOODE DO NOT PROVIDE PROVIDE INVERT PROVIDE DIRECT PROVIDE FACTO EQUIPMENT MFR APPROVED MERS | 4200 2315 3100 CURBS WITH VER T WITH 1" R-7 (3- ED/LOUVERED HA E OUTSIDE AIR HO FER COMPRESSO I DRIVE EVAPOR/ RY-INSTALLED CO R, MECHANICAL AI S THAT DO NOT M | 725 550 525 TICAL DUCT 15 TONS) OR IL GUARDS (DOD OR OPE R FOR FULL NTOR FAN, A DNVENIENCE ND DDC CON IFET SPECIE | DOAS-2 DOAS-2 DOAS-2 CONNECTION, (2" R-13 (16+ TO OR ANGLED CON NINGS. MODULATION O ND ECM MOTOR ELECTRICAL O ITRACTORS SHA | 1.5 1.5 COPPER NS) DOU NDENSEF F CAPAC COR VFD UTLETS ALL COOF ES SHALL | 4 4 4 CONDENSATE T BLE WALL CONS COILS WITH WI CITY AND ACCUR TO MODULATE TO MODULATE AT INDICATED R RDINATE PROVIS | 49.4 44.7 27.1 27.1 36.3 36.3 RAP, EXV, TOTAL STRUCTION WITH IRE GRILLES, 304 RATE LEAVING AIF FAN SPEED TO M RTUS. SEE MECHA SION AND INSTAL REORMANCE PEN | 60 35 45 Y ENCLOSED F FOAM INSULAT STAINLESS STE TEMPERATURI EET STATIC PRI NICAL ROOF PL ATION OF SEN ALTY, PAID TO (| 208-3-60 208-3-60 208-3-60 208-3-60 208-3-60 ON, AND EL DRAIN CONTR SSURE S ANS FOR GORS AN WWER | 100 100 100 DRS, SS COIL C HINGED ACCES N PANS, GALVAI OL. SETPOINT. DUC & LOCATIONS. D D SMOKE DETE | ASINGS A SS DOOR: NIZED FIL T STATIC IV. 26 TO CTORS. | 13.7 66.5 66.1 AND FREI S. TER FRA PRESSU PROVID | 95. 50. 72. EZE-STAT AMES, E-C(URE SENS(E WIRING) | 8 8 5 OPTIONS. OATED COM OR BY RTU AND POWE | 75.0/63. 75.0/63. 75.0/63. NDENSER MFR. CO R FOR TH | COILS |
| RT RT DTES: | TU-3 TU-4 TU-5 1. 2. 3. 4. 5. 6. 7. 8. 9. 10. 11. 11. | 10 5 7 PROVIDE ROOF (PROVIDE CABINE PROVIDE CABINE PROVIDE HOODE DO NOT PROVIDE PROVIDE INVERT PROVIDE DIRECT PROVIDE DIRECT PROVIDE FACTO EQUIPMENT MFR APPROVED MFRS PERFORMANCE I PROVIDE FACTO PROVIDE IBC 201 1) ATTACHMENT 2) CURB TO STRUC 3) CURB AND ATT REFER TO STRUC EQUIPMENT OR (BOTH, THE ENGII SUBMITTALS WIL PROVIDE COMBC PROVIDE FACTO | 4200 2315 3100 CURBS WITH VER T WITH 1" R-7 (3- ED/LOUVERED HA E OUTSIDE AIR HO TER COMPRESSO T DRIVE EVAPOR/ RY-INSTALLED CO R, MECHANICAL AI S THAT DO NOT M PENALTY OF \$14/ RY MOUNTED MIO 5 COMPLIANT CL OF EQUIPMENT T JCTURE. TACHMENT HARD CTURAL DRAWING CURB MANUFACT NEERED ANALYS L NOT BE APPRO D 2"/4" FILTER RAO RY E-COATING O | 725 550 525 TICAL DUCT 15 TONS) OR IL GUARDS (DOD OR OPE R FOR FULL ATOR FAN, A DNVENIENCE ND DDC CON IEET SPECIF TON FOR EV COPROCES RB AND ATT O CURB. WARE STRE GS FOR ROC URER IS ALS S AND THE E VED UNTIL A CK INTERAL CONDENSE | DOAS-2 DOAS-2 DOAS-2 DOAS-2 DOAS-2 CONNECTION, O 2" R-13 (16+ TO DR ANGLED CON 2NINGS. MODULATION O ND ECM MOTOR ELECTRICAL O ITRACTORS SHA IED EFFICIENCIE ERY 1/10 OF A P SOR CONTROLL ACHMENTS FRO NGTH. F SUBSTRATE D SO RESPONSIBL ENGINEERED INS ALL DOCUMENTA TO THE UNIT WI ER COILS WITH I | 1.5 1.5 1.5 COPPER NS) DOU VDENSEF F CAPAC COR VFD UTLETS COR VFD COR VFD C | 4 6,000 ASTM B11 | 49.4 44.7 27.1 27.1 36.3 36.3 RAP, EXV, TOTAL STRUCTION WITH IRE GRILLES, 304 RATE LEAVING AIF FAN SPEED TO M RTUS. SEE MECHA SION AND INSTAL RFORMANCE PEN EDULED IEER BAS FACE WITH DDC. URB TO STRUCTU NEERED INSTALLA SHALL BE PERFO PROVIDED ACCUF ANIZED FILTER FR IT SALT SPRAY RA | 60 35 45 Y ENCLOSED F FOAM INSULAT STAINLESS STE TEMPERATURI EET STATIC PRI NICAL ROOF PL ALTY, PAID TO GED ON A STANK RE. EQUIPMEN TION DRAWING RMED SPECIFIC ATELY. AMES WITH ME TING. | 208-3-60 208-3-60 208-3-60 208-3-60 208-3-60 ON, AND EL DRAIN CONTRE SSURE S ANS FOR SORS AN SORS FOR ORS AN OWNER. DARD UN FOR CUF S FOR IT ALLY FO RV 8 FILT | 100 100 100 100 100 00 DRS, SS COIL C HINGED ACCES N PANS, GALVAI OL. SETPOINT. DUC LOCATIONS. D D SMOKE DETE IT OF THE SAME RB MANUFACTU TEMS 1 AND 2 LI R THIS BUILDIN TERS AND ONE | ASINGS A SS DOOR: NIZED FIL T STATIC IV. 26 TO CCTORS. E CAPACI JRER IS R STED ABG G AND PF SET OF 4 | 13.7 6.5 6.1 AND FREI S. TER FRA PROVIDI TY AT AF RESPONS OVE. ROJECT : "MERV 1 | 95. 50. 72. EZE-STAT AMES, E-CO URE SENSO E WIRING WIRING HRI CONDI SIBLE FOR SIBLE FOR SIBLE FOR | 8 8 5 0 OPTIONS. 0 OATED COM OR BY RTU AND POWE TIONS. PROVIDING STAMPED A S. ADD 0.75 | 75.0/63. 75.0/63. 75.0/63. NDENSER MFR. COUR R FOR THE ENGINE | COILS COILS DRDIN E OUT ERED ED BY |
| | TU-3 TU-4 TU-5 1. 2. 3. 4. 5. 6. 7. 8. 9. 10. 11. 11. 12. 13. 14. | 10 5 7 PROVIDE ROOF (PROVIDE CABINE PROVIDE CABINE PROVIDE HOODE DO NOT PROVIDE PROVIDE INVERT PROVIDE DIRECT PROVIDE DIRECT PROVIDE FACTO EQUIPMENT MFR APPROVED MFRS PERFORMANCE I PROVIDE FACTO PROVIDE FACTO PROVIDE IBC 201 1) ATTACHMENT 2) CURB TO STRU 3) CURB AND ATT REFER TO STRU EQUIPMENT OR (BOTH, THE ENGII SUBMITTALS WIL PROVIDE FACTO | 4200 2315 3100 CURBS WITH VER T WITH 1" R-7 (3- ED/LOUVERED HA E OUTSIDE AIR HO TER COMPRESSO T DRIVE EVAPOR/ RY-INSTALLED CO R, MECHANICAL AI S THAT DO NOT M PENALTY OF \$14/ RY MOUNTED MIO 5 COMPLIANT CL OF EQUIPMENT T JCTURE. TACHMENT HARD CTURAL DRAWING CURB MANUFACT NEERED ANALYS L NOT BE APPRO D 2"/4" FILTER RAG | 725 550 525 TICAL DUCT 15 TONS) OR IL GUARDS (DOD OR OPE R FOR FULL ATOR FAN, A DNVENIENCE ND DDC CON IEET SPECIF TON FOR EV CROPROCES RB AND ATT O CURB. WARE STRE SS FOR ROC URER IS ALS S AND THE E VED UNTIL A CONDENSE | DOAS-2 DOAS-2 DOAS-2 DOAS-2 DOAS-2 CONNECTION, C 2" R-13 (16+ TO DR ANGLED COM ININGS. MODULATION O ND ECM MOTOR ELECTRICAL O ITRACTORS SHA IED EFFICIENCIE ERY 1/10 OF A P SOR CONTROLL ACHMENTS FRO NGTH. OF SUBSTRATE D SO RESPONSIBL ENGINEERED INS ALL DOCUMENTA TO THE UNIT WI ER COILS WITH N | 1.5 1.5 1.5 COPPER NS) DOU VDENSEF F CAPAC COR VFD UTLETS COR VFD UTLETS SHALL OINT LOV LER, AND DM UNIT DETAILS. E FOR PF STALLAT ATION LIS TH ONE S WINIMUM | 4 | 49.4 44.7 27.1 27.1 36.3 36.3 RAP, EXV, TOTAL STRUCTION WITH IRE GRILLES, 304 RATE LEAVING AIF FAN SPEED TO M RTUS. SEE MECHA SION AND INSTAL RFORMANCE PEN EDULED IEER BAS FACE WITH DDC. URB TO STRUCTU NEERED INSTALL/ SHALL BE PERFO PROVIDED ACCUF ANIZED FILTER FF I7 SALT SPRAY R/ | 60 35 45 Y ENCLOSED F FOAM INSULAT STAINLESS STE TEMPERATURI EET STATIC PRINICAL ROOF PL NICAL ROOF PL ATION OF SEN ALTY, PAID TO ED ON A STAND RE. EQUIPMEN TION DRAWING RMED SPECIFIC ATELY. AMES WITH ME TING. | 208-3-60 208-3-60 208-3-60 208-3-60 208-3-60 ON, AND EL DRAIN CONTR SSURE S ANS FOR SORS AN SORS AN SO | 100 100 100 100 100 100 00 01000 01000 010000 010000 0100000 01000000 01000000000 010000000000000 0100000000000000000000000000000000000 | ASINGS A SS DOOR: NIZED FIL T STATIC IV. 26 TO CTORS. E CAPACI JRER IS R STED ABC IG AND PF SET OF 4 | 13.7 6.5 6.1 AND FREI S. TER FRA PROVIDI TY AT AF RESPONS OVE. ROJECT : "MERV 1 | 95. 50. 72. EZE-STAT AMES, E-CO URE SENSO E WIRING WIRING HRI CONDI SIBLE FOR SIBLE FOR SITE AND 14 FILTERS | 8 8 8 5 OPTIONS. OATED COM OR BY RTU AND POWE TIONS. PROVIDING STAMPED A S. ADD 0.75 | 75.0/63. 75.0/63. 75.0/63. NDENSER MFR. COOR R FOR TH SENGINE | COILS COILS COILS CRDIN E OUT ERED ED BY RE DF |
| | TU-3 TU-4 TU-5 1. 2. 3. 4. 5. 6. 7. 8. 9. 10. 11. 11. 12. 13. 14. | 10 5 7 PROVIDE ROOF O PROVIDE CABINE PROVIDE CABINE PROVIDE HOODE DO NOT PROVIDE PROVIDE INVERT PROVIDE DIRECT PROVIDE FACTO EQUIPMENT MFR APPROVED MFRS PERFORMANCE I PROVIDE FACTO PROVIDE IBC 201 1) ATTACHMENT 2) CURB TO STRU 3) CURB TO STRU 3) CURB AND ATT REFER TO STRU EQUIPMENT OR O BOTH, THE ENGIN SUBMITTALS WIL PROVIDE FACTO PROVIDE FACTO | 4200 2315 3100 CURBS WITH VER T WITH 1" R-7 (3- ED/LOUVERED HA E OUTSIDE AIR HO FER COMPRESSO I DRIVE EVAPOR/ RY-INSTALLED CO R, MECHANICAL AI S THAT DO NOT N PENALTY OF \$14/ RY MOUNTED MIO 5 COMPLIANT CL OF EQUIPMENT T JCTURE. TACHMENT HARD CTURAL DRAWING CURB MANUFACT NEERED ANALYSI L NOT BE APPRO D 2"/4" FILTER RAG RY E-COATING O | 725 550 525 TICAL DUCT 15 TONS) OR IL GUARDS (DOD OR OPE R FOR FULL ATOR FAN, A DIVENIENCE ND DDC CON IEET SPECIF TON FOR EV CROPROCES RB AND ATT O CURB. WARE STRE SS FOR ROC URER IS ALS S AND THE F VED UNTIL A CK INTERAL CONDENSE DULE | DOAS-2 DOAS-2 DOAS-2 DOAS-2 DOAS-2 CONNECTION, (2" R-13 (16+ TO DR ANGLED CON ININGS. MODULATION O ND ECM MOTOR ELECTRICAL O ITRACTORS SHA IED EFFICIENCIE ERY 1/10 OF A P SOR CONTROLL ACHMENTS FRO NGTH. DF SUBSTRATE E SO RESPONSIBL ENGINEERED INIS ALL DOCUMENTA TO THE UNIT WI ER COILS WITH N | 1.5 1.5 1.5 COPPER NS) DOU VDENSEF F CAPAC COR VFD UTLETS ALL COOF ES SHALI OINT LOV LER, AND DM UNIT DETAILS. E FOR PF STALLAT ATION LIS TH ONE S MINIMUM | 4 4 4 CONDENSATE T BLE WALL CONS COILS WITH WI COILS WITH WI COILS WITH WI COILS WITH WI COILS WITH WI COILS WITH WI COULS WITH WI COULATE AND ACCUR AT INDICATED R ROUNDICATED R BACNET INTER TO CURB AND C BACNET INTER TO CURB AND C ROVIDING ENGIN ION DRAWINGS STED ABOVE IS F SET OF 2" GALVA 16,000 ASTM B11 | 49.4 44.7 27.1 27.1 36.3 36.3 RAP, EXV, TOTAL STRUCTION WITH IRE GRILLES, 304 RATE LEAVING AIF FAN SPEED TO M RTUS. SEE MECHA SION AND INSTAL RFORMANCE PEN EDULED IEER BAS FACE WITH DDC. URB TO STRUCTU NEERED INSTALL/ SHALL BE PERFO PROVIDED ACCUF ANIZED FILTER FFI 7 SALT SPRAY R/ | 60 35 45 Y ENCLOSED F FOAM INSULAT STAINLESS STE TEMPERATURI EET STATIC PRINICAL ROOF PL ATION OF SEN ALTY, PAID TO ED ON A STANI RE. EQUIPMEN TION DRAWING RMED SPECIFIC ATELY. AMES WITH ME TING. | 208-3-60 208-3-60 208-3-60 208-3-60 208-3-60 ON, AND EL DRAIN SCONTR SSURE S ANS FOR SORS AN WNER. ANS FOR SORS AN WNER. ANS FOR IT ALLY FO RV 8 FILT | 100 100 100 100 100 100 00 01 01 02 03 04 05 05 100 06 100 07 100 08 100 | ASINGS A ASINGS A SS DOOR: NIZED FIL T STATIC IV. 26 TO CTORS. E CAPACI JRER IS R STED ABC IG AND PF SET OF 4 MODEL | 13.7 16.5 16.1 AND FREI S. TER FRA PROVIDI TY AT AH RESPONS OVE. ROJECT : "MERV 1 | 95. 50. 72. EZE-STAT AMES, E-CO URE SENSO E WIRING / HRI CONDI SIBLE FOR SIBLE FOR SITE AND SITE AND S | 8 8 5 OPTIONS. OATED COM OR BY RTU AND POWE TIONS. PROVIDING STAMPED A S. ADD 0.75 | 75.0/63. 75.0/63. 75.0/63. NDENSER MFR. COOR R FOR TH S ENGINE AND SEAL " PRESSL | |
| | TU-3 TU-4 TU-5 1. 2. 3. 4. 5. 6. 7. 8. 9. 10. 11. 11. 12. 13. 14. | 10 5 7 PROVIDE ROOF (PROVIDE CABINE PROVIDE CABINE PROVIDE HOODE DO NOT PROVIDE PROVIDE INVERT PROVIDE DIRECT PROVIDE DIRECT PROVIDE FACTO EQUIPMENT MFR APPROVED MFRS PERFORMANCE I PROVIDE FACTO PROVIDE FACTO PROVIDE FACTO ORD STRUC EQUIPMENT OR (BOTH, THE ENGII SUBMITTALS WIL PROVIDE FACTO PROVIDE FACTO | 4200 2315 3100 CURBS WITH VER T WITH 1" R-7 (3- ED/LOUVERED HA E OUTSIDE AIR HO FER COMPRESSO I DRIVE EVAPOR/ RY-INSTALLED CO R, MECHANICAL AI S THAT DO NOT M PENALTY OF \$14/ RY MOUNTED MIO 5 COMPLIANT CL OF EQUIPMENT T JCTURE. TACHMENT HARD CTURAL DRAWING CURB MANUFACT NEERED ANALYS L NOT BE APPRO D 2"/4" FILTER RAO RY E-COATING O CHECC | 725 550 525 TICAL DUCT 15 TONS) OR 11 GUARDS (C COD OR OPE R FOR FULL TOR FAN, A DNVENIENCE ND DDC CON 16 ET SPECIF TON FOR EV CROPROCES RB AND ATT 10 CURB. WARE STRE 35 FOR ROC URER IS ALS 5 AND THE E VED UNTIL A CK INTERAL CONDENSE OULE OW (%) | DOAS-2 DOAS-2 DOAS-2 DOAS-2 DOAS-2 DOAS-2 CONNECTION, O 2" R-13 (16+ TO DR ANGLED CON ININGS. MODULATION O ND ECM MOTOR ELECTRICAL O ITRACTORS SHA IED EFFICIENCIE ERY 1/10 OF A P SOR CONTROLL ACHMENTS FRO NGTH. F SUBSTRATE D SO RESPONSIBL ENGINEERED INS ALL DOCUMENTA TO THE UNIT WI ER COILS WITH N ER COILS WITH N | 1.5 1.5 1.5 1.5 1.5 COPPER NS) DOU VDENSEF F CAPAC Q OR VFD UTLETS VITLETS ALL COOF ES SHALL OINT LOV LER, AND DM UNIT DETAILS. E FOR PF STALLAT ATION LISS TH ONE S MINIMUM /H | 4 6000 ASTM B11 4 6,000 ASTM B11 4 1 | 49.4 44.7 27.1 27.1 36.3 36.3 RAP, EXV, TOTAL STRUCTION WITH IRE GRILLES, 304 RATE LEAVING AIF FAN SPEED TO M RTUS. SEE MECHA SION AND INSTAL RFORMANCE PEN EDULED IEER BAS FACE WITH DDC. URB TO STRUCTU NEERED INSTALLA SHALL BE PERFO PROVIDED ACCUF ANIZED FILTER FF 7 SALT SPRAY RA | 60 35 45 Y ENCLOSED F FOAM INSULAT FOAM INSULAT STAINLESS STE TEMPERATURI ET STATIC PRINICAL ROOF PL ALTON OF SEN ALTY, PAID TO 0 ED ON A STAND RE. EQUIPMEN TION DRAWING RED SPECIFIC ATELY. AMES WITH ME TING. AT MANUFAC | 208-3-60 208-3-60 208-3-60 208-3-60 208-3-60 ON, AND EL DRAIN CONTR SSURE S ANS FOR SORS AN SORS AN SO | 100 100 100 100 100 100 DRS, SS COIL C HINGED ACCES N PANS, GALVAI OL. SETPOINT. DUC LOCATIONS. D D SMOKE DETE IT OF THE SAME RB MANUFACTU TEMS 1 AND 2 LI R THIS BUILDIN TERS AND ONE TITUS MODEL | ASINGS A ASINGS A SS DOOR: NIZED FIL T STATIC IV. 26 TO CTORS. E CAPACI JRER IS R STED ABC G AND PF SET OF 4 MODEL SIZE | 13.7 6.5 6.1 AND FREI S. TER FRA PROVIDI TY AT AF RESPONS OVE. ROJECT : "MERV 1 MERV 1 | 95. 50. 72. EZE-STAT AMES, E-CO URE SENSO E WIRING HRI CONDI SIBLE FOR SIBLE FOR 14 FILTERS | 8 8 8 5 OPTIONS. OATED COM OR BY RTU AND POWE TIONS. PROVIDING STAMPED A S. ADD 0.75 | 75.0/63. 75.0/63. 75.0/63. NDENSER MFR. COO R FOR TH B ENGINE AND SEAL " PRESSU | COILS COILS DRDIN IE OUT ERED ED BY IRE DF |
| | TU-3 TU-4 TU-5 1. 2. 3. 4. 5. 6. 7. 8. 9. 10. 11. 11. 12. 13. 14. Mark <i>Mark</i> <i>(AV-1-1)</i> | 10 5 7 PROVIDE ROOF O PROVIDE CABINE PROVIDE CABINE PROVIDE HOODE DO NOT PROVIDE PROVIDE INVERT PROVIDE DIRECT PROVIDE DIRECT PROVIDE FACTOO EQUIPMENT MFR APPROVED MFRS PERFORMANCE I PROVIDE FACTOO PROVIDE FACTOO PROVIDE FACTOO PROVIDE FACTOO SUBMITTALS WIL PROVIDE COMBO PROVIDE FACTOO PROVIDE FACTOO PROVIDE FACTOO PROVIDE FACTOO PROVIDE FACTOO | 4200 2315 3100 CURBS WITH VER ET WITH 1" R-7 (3- ED/LOUVERED HA E OUTSIDE AIR HO TER COMPRESSO I DRIVE EVAPORA RY-INSTALLED CO RY-INSTALLED CO COMPLIANT CL OF EQUIPMENT I JCTURE. IACHMENT HARD CTURAL DRAWING CURB MANUFACT NEERED ANALYS L NOT BE APPRO O 2"/4" FILTER RAC RY E-COATING O CCHECC MIN. COOLING FI 30% 30% | 725 550 525 TICAL DUCT 15 TONS) OR IL GUARDS (DOD OR OPE R FOR FULL ATOR FAN, A DIVENIENCE ND DDC CON IEET SPECIF TON FOR EV CROPROCES RB AND ATT O CURB. WARE STRE SS FOR ROC URER IS ALS S AND THE E VED UNTIL A CK INTERAL CONDENSE OULE OW (%) | DOAS-2 DOAS-2 DOAS-2 DOAS-2 DOAS-2 DOAS-2 CONNECTION, C 2" R-13 (16+ TO DR ANGLED CON NO ECM MOTOR ELECTRICAL O ITRACTORS SHA IED EFFICIENCIE ERY 1/10 OF A P SOR CONTROLL ACHMENTS FRO NGTH. F SUBSTRATE I SO RESPONSIBL ENGINEERED IN: ALL DOCUMENTA TO THE UNIT WI ER COILS WITH N ER COILS WITH N CONTROLLS WITH N C | 1.5 1.5 1.5 1.5 1.5 COPPER NS) DOU VDENSEF F CAPAC COR VFD UTLETS ALL COOF ES SHALI OINT LO' ER, AND DM UNIT DETAILS. E FOR PF STALLAT ATION LIS TH ONE S MINIMUM /H E Z | 4 6000 ASTM B11 4 100 DRAWINGS 510 ABOVE IS F 520 KW 2.5 kW 5.0 kW | 49.4 44.7 27.1 27.1 36.3 36.3 RAP, EXV, TOTAL STRUCTION WITH IRE GRILLES, 304 RATE LEAVING AIF FAN SPEED TO M RTUS. SEE MECHA SION AND INSTAL RFORMANCE PEN EDULED IEER BAS FACE WITH DDC. URB TO STRUCTU NEERED INSTALLA SHALL BE PERFO PROVIDED ACCUF ANIZED FILTER FF 7 SALT SPRAY RA ELECTRICAL HE STEPS 2 3 | 60 35 45 AT MANUFAC | 208-3-60 208-3-60 208-3-60 208-3-60 208-3-60 208-3-60 ON, AND EL DRAIN CONTR SSURE S ANS FOR SORS AN DWNER. DARD UN F OR CUF S FOR IT ALLY FO RV 8 FILT FURER | 100 100 100 100 100 100 DRS, SS COIL C HINGED ACCES N PANS, GALVAI OL. SETPOINT. DUC LOCATIONS. D D SMOKE DETE IT OF THE SAME RB MANUFACTL THIS BUILDIN TERS AND ONE ITITUS MODEL DESV DESV | ASINGS A ASINGS A SS DOOR: NIZED FIL T STATIC IV. 26 TO CTORS. E CAPACI JRER IS R STED ABC G AND PF SET OF 4 MODEL SIZE 08 08 08 | 13.7 16.5 16.1 AND FREI S. TER FRA PROVIDI TY AT AF RESPONS OVE. ROJECT : "MERV 1 MERV 1 ALL ALL | 95. 50. 72. EZE-STAT AMES, E-CO URE SENSO E WIRING A HRI CONDI SIBLE FOR SIBLE FOR SITE AND S 14 FILTERS | 8 8 5 0 OPTIONS. 0 OATED COM OR BY RTU AND POWE TIONS. PROVIDING STAMPED A S. ADD 0.75 | 75.0/63. 75.0/63. 75.0/63. NDENSER MFR. COO R FOR TH E ENGINE CON R FOR TH E ENGINE ND SEAL THE SSL | |
| | TU-3 TU-4 TU-5 1. 2. 3. 4. 5. 6. 7. 8. 9. 10. 11. 11. 12. 13. 14. 14. AV-1-1 <i>AV-1-2</i> <i>AV-1-3</i> <i>AV-1-4</i> | 10 5 7 PROVIDE ROOF O PROVIDE CABINE PROVIDE CABINE PROVIDE HOODE DO NOT PROVIDE PROVIDE INVERT PROVIDE DIRECT PROVIDE DIRECT PROVIDE FACTO EQUIPMENT MFR APPROVED MFRS PERFORMANCE I PROVIDE FACTO PROVIDE FACTO PROVIDE IBC 201 1) ATTACHMENT 2) CURB TO STRU 3) CURB AND ATT REFER TO STRU EQUIPMENT OR O BOTH, THE ENGIN SUBMITTALS WIL PROVIDE FACTO OX SO Actual Supply Air Flow 430 CFM 885 CFM 745 CFM 300 CFM | 4200 2315 3100 CURBS WITH VER ET WITH 1" R-7 (3- ED/LOUVERED HA E OUTSIDE AIR HO TER COMPRESSO I DRIVE EVAPOR/ RY-INSTALLED CO R, MECHANICAL AI S THAT DO NOT M PENALTY OF \$14/ RY MOUNTED MIO 5 COMPLIANT CL OF EQUIPMENT T JCTURE. TACHMENT HARD CTURAL DRAWING CURB MANUFACT NEERED ANALYS L NOT BE APPRO D 2"/4" FILTER RAO RY E-COATING O CHEC MIN. COOLING FI 30% 30% 30% 30% | 725 550 525 TICAL DUCT 15 TONS) OR IL GUARDS (DOD OR OPE R FOR FULL TOR FAN, A DNVENIENCE ND DDC CON IEET SPECIF TON FOR EV CROPROCES RB AND ATT O CURB. WARE STRE SS FOR ROC URER IS ALS S AND THE E VED UNTIL A CK INTERAL CONDENSE DULE OW (%) | DOAS-2 DOAS-2 DOAS-2 DOAS-2 DOAS-2 DOAS-2 CONNECTION, C 2" R-13 (16+ TO DR ANGLED CON ININGS. MODULATION O ND ECM MOTOR ELECTRICAL O ITRACTORS SHA IED EFFICIENCIE ERY 1/10 OF A P SOR CONTROLL ACHMENTS FRO NGTH. F SUBSTRATE D SOR CONTROLL ACHMENTS FRO NGTH. F SUBSTRATE D SOR CONTROLL ACHMENTS FRO DISTRATE D SOR CONTROLL ACHMENTS FRO D SOR CONTROLL ACHMENTS FRO D SO | 1.5 1.5 1.5 1.5 1.5 1.5 COPPER NS) DOU VDENSEF F CAPAC COR VFD UTLETS ALL COOF ES SHALL OINT LO' DETAILS. E FOR PF STALLAT ATION LIS TH ONE S MINIMUM /H Z Z Z Z | 4 4 <td>49.4 44.7 27.1 27.1 36.3 36.3 RAP, EXV, TOTAL STRUCTION WITH IRE GRILLES, 304 STRUCTION WITH REAR GRILLES, 304 STRUCTION WITH REAR GRILLES, 304 STRUCTION WITH REAR GRILLES, 304 STRUCTION WITH REC GRILLES, 304 STRUCTION WITH REC GRILLES, 304 STRUCTION WITH REC GRILLES, SEE MECHA STON AND INSTAL STON AND INSTAL RFORMANCE PENEDULED IEER BAS FACE WITH DDC. URB TO STRUCTU NEEERED INSTALL/ SHALL BE PERFO PROVIDED ACCUF ANIZED FILTER FF 7 SALT SPRAY R/ STEPS 2 3 3 3 3 3</td> <td>60 35 45 Y ENCLOSED F FOAM INSULAT STAINLESS STE TEMPERATURI EET STATIC PRI NICAL ROOF PL ATION OF SEN ALTY, PAID TO 0 ED ON A STANI RE. EQUIPMEN TION DRAWING RMED SPECIFIC ATELY. AMES WITH ME TING. AT MANUFAC Titu Titu Titu</td> <td>208-3-60 208-3-60 208-3-60 208-3-60 208-3-60 208-3-60 CONTR SORS AN SORS AN SORS AN SORS AN SORS AN WNER. ANS FOR SORS AN CONTRUST CONTRUST SORS AN CONTRUST CONTRUST SORS AN CONTRUST CONTRUST SORS AN CONTRUST CONTRUST SORS AN CONTRUST SORS AN CONTRUST</td> <td>100 100 100 100 100 100 DRS, SS COIL C HINGED ACCES N PANS, GALVAI OL. SETPOINT. DUC LOCATIONS. D D SMOKE DETE IT OF THE SAME RB MANUFACTU EMS 1 AND 2 LI R THIS BUILDIN TERS AND ONE DESV DESV DESV DESV DESV DESV</td> <td>ASINGS A ASINGS A SS DOOR: NIZED FIL T STATIC IV. 26 TO CTORS. E CAPACI JRER IS R STED ABC G AND PF SET OF 4 MODEL SIZE 08 08 12 08</td> <td>13.7 16.5 16.1 IND FREI S. TER FRA PROVIDI TY AT AH RESPONS OVE. ROJECT " MERV 1 MERV 1 MERV 1 ALL ALL ALL ALL</td> <td>95. 50. 72. EZE-STAT AMES, E-CO URE SENSO E WIRING / HRI CONDI SIBLE FOR SITE AND S 14 FILTERS</td> <td>8 8 5 0 OPTIONS. 0 OATED CON OR BY RTU AND POWE TIONS. PROVIDING STAMPED A S. ADD 0.75</td> <td>75.0/63. 75.0/63. 75.0/63. NDENSER MFR. COOR R FOR TH E ENGINE ND SEAL PRESSL</td> <td>COILS COILS DRDIN ERED I ERED I ERED I IRE DR</td> | 49.4 44.7 27.1 27.1 36.3 36.3 RAP, EXV, TOTAL STRUCTION WITH IRE GRILLES, 304 STRUCTION WITH REAR GRILLES, 304 STRUCTION WITH REAR GRILLES, 304 STRUCTION WITH REAR GRILLES, 304 STRUCTION WITH REC GRILLES, 304 STRUCTION WITH REC GRILLES, 304 STRUCTION WITH REC GRILLES, SEE MECHA STON AND INSTAL STON AND INSTAL RFORMANCE PENEDULED IEER BAS FACE WITH DDC. URB TO STRUCTU NEEERED INSTALL/ SHALL BE PERFO PROVIDED ACCUF ANIZED FILTER FF 7 SALT SPRAY R/ STEPS 2 3 3 3 3 3 | 60 35 45 Y ENCLOSED F FOAM INSULAT STAINLESS STE TEMPERATURI EET STATIC PRI NICAL ROOF PL ATION OF SEN ALTY, PAID TO 0 ED ON A STANI RE. EQUIPMEN TION DRAWING RMED SPECIFIC ATELY. AMES WITH ME TING. AT MANUFAC Titu Titu Titu | 208-3-60 208-3-60 208-3-60 208-3-60 208-3-60 208-3-60 CONTR SORS AN SORS AN SORS AN SORS AN SORS AN WNER. ANS FOR SORS AN CONTRUST CONTRUST SORS AN CONTRUST CONTRUST SORS AN CONTRUST CONTRUST SORS AN CONTRUST CONTRUST SORS AN CONTRUST SORS AN CONTRUST | 100 100 100 100 100 100 DRS, SS COIL C HINGED ACCES N PANS, GALVAI OL. SETPOINT. DUC LOCATIONS. D D SMOKE DETE IT OF THE SAME RB MANUFACTU EMS 1 AND 2 LI R THIS BUILDIN TERS AND ONE DESV DESV DESV DESV DESV DESV | ASINGS A ASINGS A SS DOOR: NIZED FIL T STATIC IV. 26 TO CTORS. E CAPACI JRER IS R STED ABC G AND PF SET OF 4 MODEL SIZE 08 08 12 08 | 13.7 16.5 16.1 IND FREI S. TER FRA PROVIDI TY AT AH RESPONS OVE. ROJECT " MERV 1 MERV 1 MERV 1 ALL ALL ALL ALL | 95. 50. 72. EZE-STAT AMES, E-CO URE SENSO E WIRING / HRI CONDI SIBLE FOR SITE AND S 14 FILTERS | 8 8 5 0 OPTIONS. 0 OATED CON OR BY RTU AND POWE TIONS. PROVIDING STAMPED A S. ADD 0.75 | 75.0/63. 75.0/63. 75.0/63. NDENSER MFR. COOR R FOR TH E ENGINE ND SEAL PRESSL | COILS COILS DRDIN ERED I ERED I ERED I IRE DR |
| | TU-3 TU-4 TU-5 1. 2. 3. 4. 5. 6. 7. 8. 9. 10. 11. 11. 12. 13. 14. 14. AV-1-1 <i>(AV-1-2)</i> <i>(AV-1-2)</i> <i>(AV-1-3)</i> <i>(AV-1-3)</i> <i>(AV-1-4)</i> <i>(AV-1-5)</i> <i>(AV-1-6)</i> | 10 5 7 PROVIDE ROOF (PROVIDE CABINE PROVIDE CABINE PROVIDE HOODE DO NOT PROVIDE PROVIDE INVERT PROVIDE DIRECT PROVIDE DIRECT PROVIDE FACTO EQUIPMENT MFR APPROVED MFRS PERFORMANCE I PROVIDE FACTO PROVIDE FACTO PROVIDE FACTO PROVIDE IBC 201 1) ATTACHMENT 2) CURB TO STRU 3) CURB AND ATT REFER TO STRU EQUIPMENT OR (BOTH, THE ENGII SUBMITTALS WIL PROVIDE COMBC PROVIDE FACTO OX SO Actual Supply Air Flow 430 CFM 885 CFM 745 CFM 300 CFM 350 CFM | 4200 2315 3100 CURBS WITH VER ET WITH 1" R-7 (3- ED/LOUVERED HA E OUTSIDE AIR HO TER COMPRESSO I DRIVE EVAPORA RY-INSTALLED CO RY-INSTALLED CO RY-INSTALLED CO RY-INSTALLED CO RY MOUNTED MIO 5 COMPLIANT CL OF EQUIPMENT 1 JCTURE. FACHMENT HARD CTURAL DRAWING CURB MANUFACT NEERED ANALYS L NOT BE APPRO D 2"/4" FILTER RAG RY E-COATING OF CHEC MIN. COOLING FI 30% 30% 30% 30% 30% | 725 550 525 TICAL DUCT 15 TONS) OR IL GUARDS (COD OR OPE R FOR FULL TOR FAN, A DNVENIENCE ND DDC CON IEET SPECIF TON FOR EV CROPROCES RB AND ATT O CURB. WARE STRE GS FOR ROC URER IS ALS S AND THE E VED UNTIL A CK INTERAL CONDENSE DULE OW (%) | DOAS-2 DOAS-2 DOAS-2 DOAS-2 DOAS-2 DOAS-2 DOAS-2 CONNECTION, C 2" R-13 (16+ TO DR ANGLED CON ININGS. MODULATION O ND ECM MOTOR ELECTRICAL O ITRACTORS SHA IED EFFICIENCIE ERY 1/10 OF A P SOR CONTROLL ACHMENTS FRO NGTH. F SUBSTRATE D SOR CONTROLL ACHMENTS FRO NGTH. F SUBSTRATE D SOR CONTROLL ACHMENTS FRO DO THE UNIT WI ER COILS WITH N ELECTRICALV/P 208 V / 3 / 60 Hz 208 V / 3 / 60 Hz | 1.5 1.5 1.5 1.5 1.5 1.5 1.5 COPPER NS) DOU VDENSEF F CAPAC COR VFD UTLETS ALL COOF ES SHALL OINT LO' DETAILS. E FOR PF STALLAT ATION LIS TH ONE S MINIMUM /H Z Z Z Z Z Z Z Z Z Z Z Z | 4 CONDENSATE T BLE WALL CONS COILS WITH WI COILS WITH PROVIS INCLUDE A PEI WER THAN SCHI BACNET INTER TO CURB AND C STED ABOVE IS F SET OF 2" GALVA 6,000 ASTM B11 4 6,000 ASTM B11 2.5 kW 2.0 kW 2.5 kW 2.0 kW | 49.4 44.7 27.1 27.1 36.3 36.3 RAP, EXV, TOTAL STRUCTION WITH STRUCTION WITH IRE GRILLES, 304 RATE LEAVING AIF FAN SPEED TO M STOR AND INSTAL RFORMANCE PEN EDULED IEER BAS FACE WITH DDC. URB TO STRUCTU NEERED INSTALL SHALL BE PERFO PROVIDED ACCUF ANIZED FILTER FF 7 SALT SPRAY R/ | 60 35 45 Y ENCLOSED F FOAM INSULAT STAINLESS STE TEMPERATURI EET STATIC PRINICAL ROOF PL ATION OF SEN ALTY, PAID TO ORDINALTY, PAID | 208-3-60 208-3-60 208-3-60 208-3-60 208-3-60 208-3-60 CONTR | 100 100 100 100 100 100 00 DRS, SS COIL C HINGED ACCES N PANS, GALVAI OL. SETPOINT. DUC LOCATIONS. D D SMOKE DETE IT OF THE SAME RB MANUFACTU TERS 1 AND 2 LI R THIS BUILDIN TERS AND ONE DESV DESV DESV DESV DESV DESV DESV | ASINGS A ASINGS A SS DOOR SS DOOR NIZED FIL T STATIC IV. 26 TO CTORS. E CAPACI JRER IS R STED ABC G AND PF SET OF 4 MODEL SIZE 08 08 08 12 08 08 08 08 08 08 08 08 08 08 | 13.7 16.5 16.1 AND FREI S. TER FRA PROVIDI TY AT AF RESPONS OVE. ROJECT "MERV 1 ALL ALL ALL ALL ALL ALL ALL | 95. 50. 72. EZE-STAT AMES, E-CO URE SENSO E WIRING HRI CONDI SIBLE FOR SIBLE FOR 14 FILTERS | 8 8 8 5 OPTIONS. 0ATED CON OATED CON 0ATED CON OR BY RTU AND POWE TIONS. PROVIDING STAMPED A S. ADD 0.75 | 75.0/63. 75.0/63. 75.0/63. 75.0/63. NDENSER MFR. COOR R FOR TH S ENGINE CONTENSION CONTENSION MAR | |
| | TU-3 TU-4 TU-5 1. 2. 3. 4. 5. 6. 7. 8. 9. 10. 11. 11. 12. 13. 14. 14. AV-1-1 <i>(AV-1-1)</i> <i>(AV-1-2)</i> <i>(AV-1-3)</i> <i>(AV-1-3)</i> <i>(AV-1-5)</i> <i>(AV-1-7)</i> <i>(AV-1-7)</i> | 10 5 7 PROVIDE ROOF O PROVIDE CABINE PROVIDE CABINE PROVIDE CABINE PROVIDE HOODE DO NOT PROVIDE PROVIDE INVERT PROVIDE DIRECT PROVIDE FACTO EQUIPMENT MFR APPROVED MFRS PERFORMANCE I PROVIDE FACTO PROVIDE FACTO PROVIDE FACTO PROVIDE IBC 201 1) ATTACHMENT 2) CURB TO STRU 3) CURB AND ATT REFER TO STRU 2) CURB TO STRU 3) CURB AND ATT REFER TO STRU EQUIPMENT OR O BOTH, THE ENGII SUBMITTALS WIL PROVIDE COMBO PROVIDE FACTO OX SO Actual Supply Air Flow 430 CFM 835 CFM 300 CFM 375 CFM 350 CFM 815 CFM | 4200 2315 3100 CURBS WITH VER ET WITH 1" R-7 (3- ED/LOUVERED HA E OUTSIDE AIR HO FER COMPRESSO I DRIVE EVAPOR/ RY-INSTALLED CO RY-INSTALLED CO RY-INSTALLED CO RY-INSTALLED CO RY MOUNTED MIC 5 COMPLIANT CL OF EQUIPMENT 1 JCTURE. IACHMENT HARD CTURAL DRAWING CURB MANUFACT NEERED ANALYS L NOT BE APPRO D 2"/4" FILTER RAO RY E-COATING O CHEC MIN. COOLING FI 30% 30% 30% 30% 30% 30% 30% 30% | 725 550 525 TICAL DUCT 15 TONS) OR IL GUARDS (DOD OR OPE R FOR FULL ATOR FAN, A DIVENIENCE ND DDC CON IEET SPECIF TON FOR EV CROPROCES RB AND ATT 0 CURB. WARE STRE SS FOR ROC URER IS ALS S AND THE E VED UNTIL A CK INTERAL CONDENSE DULE | DOAS-2 DOAS-2 DOAS-2 DOAS-2 DOAS-2 DOAS-2 CONNECTION, C 2" R-13 (16+ TO DR ANGLED CON NO ECM MOTOR ELECTRICAL O ITRACTORS SHA IED EFFICIENCIE ERY 1/10 OF A P SOR CONTROLL ACHMENTS FRC NGTH. F SUBSTRATE I SO RESPONSIBL ENGINEERED IN: ALL DOCUMENTA TO THE UNIT WI ER COILS WITH N ELECTRICALV/PA 208 V / 3 / 60 Hz 208 V / 3 / 60 Hz | 1.5 1.5 1.5 1.5 1.5 1.5 1.5 COPPER NS) DOU VDENSEF F CAPAC COR VFD UTLETS ALL COOF ES SHALI OINT LOV EF CAPAC OINT LOV EF CAPAC OINT LOV EF CAPAC MUNIT DETAILS. E FOR PF STALLAT ATION LIS TH ONE S MINIMUM /H Z <t< td=""><td>4 5 6,000 ASTM B11 4 6,000 ASTM B11 4 4.5 kW 2.0 kW 4.5 kW 2.0 kW 4.5 kW</td><td>49.4 44.7 27.1 27.1 36.3 36.3 RAP, EXV, TOTAL STRUCTION WITH IRE GRILLES, 304 ATE LEAVING AIF FAN SPEED TO M STUS. SEE MECHA SION AND INSTAL RFORMANCE PEN EDULED IEER BAS FACE WITH DDC. URB TO STRUCTU NEERED INSTALL/ SHALL BE PERFO PROVIDED ACCUF ANIZED FILTER FF 7 SALT SPRAY R/ 2 3 3 1 2 3 3 1 3 3 3</td><td>60 35 45 AT MANUFAC AT MANUFAC AT MANUFAC Titu Titu</td><td>208-3-60 208-3-60 208-3-60 208-3-60 208-3-60 208-3-60 AN MOTO ON, AND EL DRAIN CONTR SSURE S ANS FOR SORS AN WNER. WARD UN F OR CUF S FOR IT ALLY FO RV 8 FILT TURER 5 5 5 5 5 5 5 5 5 5 5 5 5</td><td>100 100 100 100 100 100 00 01000 01000 01000 01000 01000 01000 01000 01000 01000 01000 01000 01000</td><td>ASINGS A SS DOOR: NIZED FIL T STATIC IV. 26 TO CTORS. E CAPACI JRER IS R STED ABC G AND PF SET OF 4 MODEL SIZE 08 08 08 08 08 08 14 14</td><td>13.7 13.7 16.5 16.1 IND FREI S. TER FRA PROVIDI TY AT AF RESPONS OVE. ROJECT : "MERV 1 MERV 1 MERV 1 ALL ALL ALL ALL ALL ALL</td><td>95. 50. 72. EZE-STAT AMES, E-CO URE SENSO E WIRING A HRI CONDI SIBLE FOR SIBLE FOR SITE AND S 14 FILTERS</td><td>8 8 8 5 OPTIONS. 0 OATED CON OR BY RTU AND POWE TIONS. PROVIDING STAMPED A S. ADD 0.75</td><td>75.0/63. 75.0/63. 75.0/63. NDENSER MFR. COOR R FOR THE ENGINE NOT SEAL PRESSL</td><td>COILS COILS</td></t<> | 4 5 6,000 ASTM B11 4 6,000 ASTM B11 4 4.5 kW 2.0 kW 4.5 kW 2.0 kW 4.5 kW | 49.4 44.7 27.1 27.1 36.3 36.3 RAP, EXV, TOTAL STRUCTION WITH IRE GRILLES, 304 ATE LEAVING AIF FAN SPEED TO M STUS. SEE MECHA SION AND INSTAL RFORMANCE PEN EDULED IEER BAS FACE WITH DDC. URB TO STRUCTU NEERED INSTALL/ SHALL BE PERFO PROVIDED ACCUF ANIZED FILTER FF 7 SALT SPRAY R/ 2 3 3 1 2 3 3 1 3 3 3 | 60 35 45 AT MANUFAC AT MANUFAC AT MANUFAC Titu | 208-3-60 208-3-60 208-3-60 208-3-60 208-3-60 208-3-60 AN MOTO ON, AND EL DRAIN CONTR SSURE S ANS FOR SORS AN WNER. WARD UN F OR CUF S FOR IT ALLY FO RV 8 FILT TURER 5 5 5 5 5 5 5 5 5 5 5 5 5 | 100 100 100 100 100 100 00 01000 01000 01000 01000 01000 01000 01000 01000 01000 01000 01000 01000 | ASINGS A SS DOOR: NIZED FIL T STATIC IV. 26 TO CTORS. E CAPACI JRER IS R STED ABC G AND PF SET OF 4 MODEL SIZE 08 08 08 08 08 08 14 14 | 13.7 13.7 16.5 16.1 IND FREI S. TER FRA PROVIDI TY AT AF RESPONS OVE. ROJECT : "MERV 1 MERV 1 MERV 1 ALL ALL ALL ALL ALL ALL | 95. 50. 72. EZE-STAT AMES, E-CO URE SENSO E WIRING A HRI CONDI SIBLE FOR SIBLE FOR SITE AND S 14 FILTERS | 8 8 8 5 OPTIONS. 0 OATED CON OR BY RTU AND POWE TIONS. PROVIDING STAMPED A S. ADD 0.75 | 75.0/63. 75.0/63. 75.0/63. NDENSER MFR. COOR R FOR THE ENGINE NOT SEAL PRESSL | COILS |
| | TU-3 TU-4 TU-5 1. 2. 3. 4. 5. 6. 7. 8. 9. 10. 11. 12. 13. 14. AV-1-1 AV-1-2 AV-1-2 AV-1-3 AV-1-4 AV-1-5 AV-1-6 AV-1-7 AV-1-8 AV-2-1 | 10 5 7 PROVIDE ROOF O PROVIDE ROOF O PROVIDE CABINE PROVIDE CABINE PROVIDE HOODE DO NOT PROVIDE PROVIDE INVERT PROVIDE DIRECT PROVIDE FACTO EQUIPMENT MFR APPROVED MFRS PERFORMANCE I PROVIDE FACTO PROVIDE FACTO PROVIDE IBC 201 1) ATTACHMENT 2) CURB TO STRU 3) CURB AND ATT REFER TO STRU 2) CURB TO STRU 3) CURB AND ATT REFER TO STRU EQUIPMENT OR O BOTH, THE ENGIN SUBMITTALS WIL PROVIDE COMBO PROVIDE FACTO OX SO Actual Supply Air Flow 430 CFM 885 CFM 300 CFM 375 CFM 300 CFM 315 CFM | 4200 2315 3100 CURBS WITH VER ET WITH 1" R-7 (3- ED/LOUVERED HA E OUTSIDE AIR HO TER COMPRESSO I DRIVE EVAPOR/ RY-INSTALLED CO R, MECHANICAL AI S THAT DO NOT M PENALTY OF \$14/ RY MOUNTED MIO IS COMPLIANT CL OF EQUIPMENT T JCTURE. TACHMENT HARD CTURAL DRAWING CURB MANUFACT NEERED ANALYSI L NOT BE APPRO D 2"/4" FILTER RAC RY E-COATING O CHEC MIN. COOLING FI 30% 30% 30% 30% 30% 30% 30% 30% | 725 550 525 TICAL DUCT 15 TONS) OR IL GUARDS (DOD OR OPE R FOR FULL ATOR FAN, A DNVENIENCE ND DDC CON IEET SPECIF TON FOR EV CROPROCES RB AND ATT O CURB. WARE STRE SS FOR ROC URER IS ALS S AND THE F VED UNTIL A CK INTERAL CONDENSE OULE OW (%) | DOAS-2 DOAS-2 DOAS-2 DOAS-2 DOAS-2 DOAS-2 CONNECTION, (C 2" R-13 (16+ TO DR ANGLED CON ININGS. MODULATION O ND ECM MOTOR ELECTRICAL O ITRACTORS SHA IED EFFICIENCIE ERY 1/10 OF A P SOR CONTROLL ACHMENTS FROM NGTH. OF SUBSTRATE ID SOR CONTROLL ACHMENTS FROM NGTH. DF SUBSTRATE ID SOR CONTROLL ACHMENTS FROM IL DOCUMENTA TO THE UNIT WI ER COILS WITH N CONSTRUCTION CONSTRUCTION CONSTRUCTION CONSTRUCTION DOCUMENTA DOCUMENTA DOCUMENTA DOCUMENTA DOCUMENTA CONSTRUCTION DOCUMENTA DOCUMENTA DOCUMENTA CONSTRUCTION | 1.5 1.5 1.5 1.5 1.5 1.5 1.5 1.5 COPPER NS) DOU VDENSEF F CAPAC R OR VFD UTLETS ALL COOF ES SHALL OINT LOV LER, AND DM UNIT DETAILS. E FOR PF STALLAT ATION LIS TH ONE S MINIMUM /H Z <td>4 4 <td>49.4 44.7 27.1 27.1 36.3 36.3 RAP, EXV, TOTAL STRUCTION WITH IRE GRILLES, 304 ATE LEAVING AIF FAN SPEED TO M SEE MECHA SION AND INSTAL RFORMANCE PEN EDULED IEER BAS FACE WITH DDC. URB TO STRUCTU NEERED INSTALL/ SHALL BE PERFO PROVIDED ACCUF ANIZED FILTER FF 7 SALT SPRAY R/ </td><td>60 35 45 AY ENCLOSED F FOAM INSULAT STAINLESS STE TEMPERATURI EET STATIC PRINICAL ROOF PL ATION OF SEN ALTY, PAID TO GED ON A STAND RE. EQUIPMEN TION DRAWING RED SPECIFIC ATELY. AMES WITH ME TING. AT MANUFAC Titu Titu</td><td>208-3-60 208-3-60 208-3-60 208-3-60 208-3-60 208-3-60 208-3-60 EL DRAIN EL DRAIN ECONTR SSURE S ANS FOR SORS AN DWNER. ANS FOR SORS AN DWNER. ANS FOR ITOR CUF S FOR IT ALLY FO RV 8 FILT TURER 5 5 5 5 5 5 5 5 5 5 5 5 5</td><td>100 100 100 100 100 100 00 01000 01000</td><td>ASINGS A SS DOOR: NIZED FIL T STATIC IV. 26 TO CTORS. E CAPACI JRER IS R STED ABC G AND PF SET OF 4 MODEL SIZE 08 08 12 08 08 12 08 08 14 14 08 08 14 14 08</td><td>13.7 13.7 16.5 16.1 IND FREI S. TER FRA PROVIDI TY AT AF RESPONS OVE. ROJECT "MERV 1 MERV 1 MERV 1 ALL ALL ALL ALL ALL ALL ALL AL</td><td>95. 50. 72. EZE-STAT AMES, E-CO URE SENSO E WIRING / HRI CONDI SIBLE FOR SITE AND SIBLE FOR 14 FILTERS</td><td>8 8 8 5 OPTIONS. OATED CON OATED CON OR BY RTU AND POWE TIONS. PROVIDING STAMPED A S. ADD 0.75 Image: Constraint of the second secon</td><td>75.0/63. 75.0/63. 75.0/63. 75.0/63. NDENSER MFR. COOR FOR THE ENGINE NO SEAL "PRESSL VIINI MAR ACCL NOTE 1. 2.</td><td>COILS COILS</td></td> | 4 4 <td>49.4 44.7 27.1 27.1 36.3 36.3 RAP, EXV, TOTAL STRUCTION WITH IRE GRILLES, 304 ATE LEAVING AIF FAN SPEED TO M SEE MECHA SION AND INSTAL RFORMANCE PEN EDULED IEER BAS FACE WITH DDC. URB TO STRUCTU NEERED INSTALL/ SHALL BE PERFO PROVIDED ACCUF ANIZED FILTER FF 7 SALT SPRAY R/ </td> <td>60 35 45 AY ENCLOSED F FOAM INSULAT STAINLESS STE TEMPERATURI EET STATIC PRINICAL ROOF PL ATION OF SEN ALTY, PAID TO GED ON A STAND RE. EQUIPMEN TION DRAWING RED SPECIFIC ATELY. AMES WITH ME TING. AT MANUFAC Titu Titu</td> <td>208-3-60 208-3-60 208-3-60 208-3-60 208-3-60 208-3-60 208-3-60 EL DRAIN EL DRAIN ECONTR SSURE S ANS FOR SORS AN DWNER. ANS FOR SORS AN DWNER. ANS FOR ITOR CUF S FOR IT ALLY FO RV 8 FILT TURER 5 5 5 5 5 5 5 5 5 5 5 5 5</td> <td>100 100 100 100 100 100 00 01000 01000</td> <td>ASINGS A SS DOOR: NIZED FIL T STATIC IV. 26 TO CTORS. E CAPACI JRER IS R STED ABC G AND PF SET OF 4 MODEL SIZE 08 08 12 08 08 12 08 08 14 14 08 08 14 14 08</td> <td>13.7 13.7 16.5 16.1 IND FREI S. TER FRA PROVIDI TY AT AF RESPONS OVE. ROJECT "MERV 1 MERV 1 MERV 1 ALL ALL ALL ALL ALL ALL ALL AL</td> <td>95. 50. 72. EZE-STAT AMES, E-CO URE SENSO E WIRING / HRI CONDI SIBLE FOR SITE AND SIBLE FOR 14 FILTERS</td> <td>8 8 8 5 OPTIONS. OATED CON OATED CON OR BY RTU AND POWE TIONS. PROVIDING STAMPED A S. ADD 0.75 Image: Constraint of the second secon</td> <td>75.0/63. 75.0/63. 75.0/63. 75.0/63. NDENSER MFR. COOR FOR THE ENGINE NO SEAL "PRESSL VIINI MAR ACCL NOTE 1. 2.</td> <td>COILS COILS</td> | 49.4 44.7 27.1 27.1 36.3 36.3 RAP, EXV, TOTAL STRUCTION WITH IRE GRILLES, 304 ATE LEAVING AIF FAN SPEED TO M SEE MECHA SION AND INSTAL RFORMANCE PEN EDULED IEER BAS FACE WITH DDC. URB TO STRUCTU NEERED INSTALL/ SHALL BE PERFO PROVIDED ACCUF ANIZED FILTER FF 7 SALT SPRAY R/ | 60 35 45 AY ENCLOSED F FOAM INSULAT STAINLESS STE TEMPERATURI EET STATIC PRINICAL ROOF PL ATION OF SEN ALTY, PAID TO GED ON A STAND RE. EQUIPMEN TION DRAWING RED SPECIFIC ATELY. AMES WITH ME TING. AT MANUFAC Titu | 208-3-60 208-3-60 208-3-60 208-3-60 208-3-60 208-3-60 208-3-60 EL DRAIN EL DRAIN ECONTR SSURE S ANS FOR SORS AN DWNER. ANS FOR SORS AN DWNER. ANS FOR ITOR CUF S FOR IT ALLY FO RV 8 FILT TURER 5 5 5 5 5 5 5 5 5 5 5 5 5 | 100 100 100 100 100 100 00 01000 01000 | ASINGS A SS DOOR: NIZED FIL T STATIC IV. 26 TO CTORS. E CAPACI JRER IS R STED ABC G AND PF SET OF 4 MODEL SIZE 08 08 12 08 08 12 08 08 14 14 08 08 14 14 08 | 13.7 13.7 16.5 16.1 IND FREI S. TER FRA PROVIDI TY AT AF RESPONS OVE. ROJECT "MERV 1 MERV 1 MERV 1 ALL ALL ALL ALL ALL ALL ALL AL | 95. 50. 72. EZE-STAT AMES, E-CO URE SENSO E WIRING / HRI CONDI SIBLE FOR SITE AND SIBLE FOR 14 FILTERS | 8 8 8 5 OPTIONS. OATED CON OATED CON OR BY RTU AND POWE TIONS. PROVIDING STAMPED A S. ADD 0.75 Image: Constraint of the second secon | 75.0/63. 75.0/63. 75.0/63. 75.0/63. NDENSER MFR. COOR FOR THE ENGINE NO SEAL "PRESSL VIINI MAR ACCL NOTE 1. 2. | COILS |
| | TU-3 TU-4 TU-5 1. 2. 3. 4. 5. 6. 7. 8. 9. 10. 11. 12. 13. 14. AV-1-1 AV-1-2 AV-1-3 AV-1-4 AV-1-5 AV-1-5 AV-1-6 AV-1-7 AV-1-8 AV-2-2 AV-2-3 | 10 5 7 PROVIDE ROOF O PROVIDE CABINE PROVIDE CABINE PROVIDE HOODE DO NOT PROVIDE PROVIDE INVERT PROVIDE DIRECT PROVIDE DIRECT PROVIDE FACTO EQUIPMENT MFR APPROVED MFRS PERFORMANCE I PROVIDE FACTO PROVIDE FACTO PROVIDE FACTO PROVIDE IBC 201 1) ATTACHMENT 2) CURB TO STRU 3) CURB AND ATTI REFER TO STRU 2) CURB TO STRU 3) CURB AND ATTI REFER TO STRU EQUIPMENT OR O BOTH, THE ENGII SUBMITTALS WIL PROVIDE COMBO PROVIDE FACTO OX S Actual Supply Air Flow A30 CFM 350 CFM 350 CFM 350 CFM 350 CFM 1100 CFM 485 CFM | 4200 2315 3100 CURBS WITH VER ET WITH 1" R-7 (3- ED/LOUVERED HA E OUTSIDE AIR HC TER COMPRESSO I DRIVE EVAPOR/ RY-INSTALLED CO R, MECHANICAL AI S THAT DO NOT M PENALTY OF \$14/ RY MOUNTED MIC IS COMPLIANT CL OF EQUIPMENT T JCTURE. FACHMENT HARD CTURAL DRAWING CURB MANUFACT NEERED ANALYS L NOT BE APPRO D 2"/4" FILTER RAC RY E-COATING O CHEC MIN. COOLING FI 30% 30% 30% 30% 30% 30% 30% 30% | 725 550 525 TICAL DUCT 15 TONS) OR IL GUARDS (DOD OR OPE R FOR FULL TOR FAN, A DNVENIENCE ND DDC CON IEET SPECIF TON FOR EV CROPROCES RB AND ATT O CURB. WARE STRE SS FOR ROC URER IS ALS S AND THE E VED UNTIL A CK INTERAL CONDENSE DULE OW (%) E | DOAS-2 DOAS-2 DOAS-2 DOAS-2 DOAS-2 DOAS-2 DOAS-2 DOAS-2 DOAS-2 CONNECTION, (2 2" R-13 (16+ TO DR ANGLED CON ININGS. MODULATION O ND ECM MOTOR ELECTRICAL O ITRACTORS SHA IED EFFICIENCIE ERY 1/10 OF A P SOR CONTROLL ACHMENTS FRO NGTH. F SUBSTRATE D SOR CONTROLL ACHMENTS FRO NGTH. F SUBSTRATE D SOR CONTROLL ACHMENTS FRO SOR CONTROLL ACHMENTS FRO DISTRATE D SOR CONTROLL ACHMENTS FRO D SOR V / 3 / 60 HZ 208 V / 3 / 60 HZ | 1.5 1.5 1.5 1.5 1.5 1.5 1.5 1.5 COPPER NS) DOU VDENSEF F CAPAC COR VFD UTLETS ALL COOF ES SHALL OINT LOV EF CAP PI STALLAT ATION LIS TH ONE S WINIMUM /H Z< | 4 4 <td>49.4 44.7 27.1 27.1 36.3 36.3 RAP, EXV, TOTAL STRUCTION WITH REGRILLES, 304 STRUCTION WITH REGRILLES, 304 STRUCTION WITH REGRILLES, 304 STRUCTION WITH REGRILLES, 304 STRUCTION WITH REGRILLES, SEE MECHA SION AND INSTAL SION AND INSTAL RFORMANCE PEN EDULED IEER BAS FACE WITH DDC. URB TO STRUCTU NEERED INSTALL/ SHALL BE PERFO PROVIDED ACCUF ANIZED FILTER FFI 7 SALT SPRAY R/ 2 3 3 1 2 3 3 1 2 3 3 3 1 2 3 3 1 2 3 3 1 3 3 3 2 3</td> <td>60 35 45 AT MANUFAC ATION DRAWING RE. EQUIPMEN TION DRAWING RE EQUIPMEN TION DRAWING TING. TING. TING. TITU TITU</td> <td>208-3-60 208-3-60 208-3-60 208-3-60 208-3-60 208-3-60 AN MOTO ON, AND EL DRAIN E CONTR SSURE S ANS FOR SORS AN WNER. ANS FOR SORS AN CONTRUST SORS AN SORS AN CONTRUST SORS AN SORS AN CONTRUST SORS AN SORS AN SORS AN SORS AN CONTRUST SORS AN SORS AN SOR</td> <td>100 100 100 100 100 100 DRS, SS COIL C HINGED ACCES N PANS, GALVAI OL. SETPOINT. DUC LOCATIONS. D D SMOKE DETE IT OF THE SAME RB MANUFACTU EMS 1 AND 2 LI R THIS BUILDIN TERS AND ONE DESV DESV</td> <td>ASINGS A SS DOOR: NIZED FIL T STATIC IV. 26 TO CTORS. E CAPACI JRER IS R STED ABC G AND PF SET OF 4 MODEL SIZE 08 08 08 12 08 08 12 08 08 14 14 14 08</td> <td>13.7 16.5 16.1 IND FREI S. TER FRA PROVIDI TY AT AF RESPONS OVE. ROJECT : "MERV 1 ALL ALL ALL ALL ALL ALL ALL AL</td> <td>95. 50. 72. EZE-STAT AMES, E-CO URE SENSO E WIRING J HRI CONDI SIBLE FOR SITE AND S 14 FILTERS</td> <td>8 8 5 0 OPTIONS. 0 OATED CON OR BY RTU AND POWE TIONS. PROVIDING STAMPED A S. ADD 0.75</td> <td>75.0/63. 75.0/63. 75.0/63. NDENSER MFR. COOR FOR TH ENGINE ND SEAL "PRESSU VIINI MAR ACCL NOTE 1. 2. 3.</td> <td>COILS COILS DRDIN ERED I ERED I ERED I IRE DR SF K J-1</td> | 49.4 44.7 27.1 27.1 36.3 36.3 RAP, EXV, TOTAL STRUCTION WITH REGRILLES, 304 STRUCTION WITH REGRILLES, 304 STRUCTION WITH REGRILLES, 304 STRUCTION WITH REGRILLES, 304 STRUCTION WITH REGRILLES, SEE MECHA SION AND INSTAL SION AND INSTAL RFORMANCE PEN EDULED IEER BAS FACE WITH DDC. URB TO STRUCTU NEERED INSTALL/ SHALL BE PERFO PROVIDED ACCUF ANIZED FILTER FFI 7 SALT SPRAY R/ 2 3 3 1 2 3 3 1 2 3 3 3 1 2 3 3 1 2 3 3 1 3 3 3 2 3 | 60 35 45 AT MANUFAC ATION DRAWING RE. EQUIPMEN TION DRAWING RE EQUIPMEN TION DRAWING TING. TING. TING. TITU | 208-3-60 208-3-60 208-3-60 208-3-60 208-3-60 208-3-60 AN MOTO ON, AND EL DRAIN E CONTR SSURE S ANS FOR SORS AN WNER. ANS FOR SORS AN CONTRUST SORS AN SORS AN CONTRUST SORS AN SORS AN CONTRUST SORS AN SORS AN SORS AN SORS AN CONTRUST SORS AN SORS AN SOR | 100 100 100 100 100 100 DRS, SS COIL C HINGED ACCES N PANS, GALVAI OL. SETPOINT. DUC LOCATIONS. D D SMOKE DETE IT OF THE SAME RB MANUFACTU EMS 1 AND 2 LI R THIS BUILDIN TERS AND ONE DESV | ASINGS A SS DOOR: NIZED FIL T STATIC IV. 26 TO CTORS. E CAPACI JRER IS R STED ABC G AND PF SET OF 4 MODEL SIZE 08 08 08 12 08 08 12 08 08 14 14 14 08 | 13.7 16.5 16.1 IND FREI S. TER FRA PROVIDI TY AT AF RESPONS OVE. ROJECT : "MERV 1 ALL ALL ALL ALL ALL ALL ALL AL | 95. 50. 72. EZE-STAT AMES, E-CO URE SENSO E WIRING J HRI CONDI SIBLE FOR SITE AND S 14 FILTERS | 8 8 5 0 OPTIONS. 0 OATED CON OR BY RTU AND POWE TIONS. PROVIDING STAMPED A S. ADD 0.75 | 75.0/63. 75.0/63. 75.0/63. NDENSER MFR. COOR FOR TH ENGINE ND SEAL "PRESSU VIINI MAR ACCL NOTE 1. 2. 3. | COILS COILS DRDIN ERED I ERED I ERED I IRE DR SF K J-1 |
| | TU-3 TU-4 TU-5 1. 2. 3. 4. 5. 6. 7. 8. 9. 10. 11. $AV B$ Mark $AV-1-1$ $AV-1-1$ $AV-1-2$ $AV-1-2$ $AV-1-2$ $AV-1-2$ $AV-1-4$ $AV-1-5$ $AV-1-5$ $AV-1-6$ $AV-2-1$ $AV-2-2$ $AV-2-3$ $AV-2-4$ $AV-2-5$ | 10 5 7 PROVIDE ROOF O PROVIDE ROOF O PROVIDE CABINE PROVIDE CABINE PROVIDE HOODE DO NOT PROVIDE PROVIDE INVERT PROVIDE DIRECT PROVIDE DIRECT PROVIDE FACTO EQUIPMENT MFR APPROVED MFRS PERFORMANCE I PROVIDE FACTO PROVIDE FACTO PROVIDE FACTO PROVIDE FACTO PROVIDE FACTO OX SO EQUIPMENT OR O BOTH, THE ENGII SUBMITTALS WIL PROVIDE FACTO BOTH, THE ENGII SUBMITTALS WIL PROVIDE FACTO OX SO Actual Supply Air Flow A30 CFM 885 CFM 300 CFM 350 CFM 350 CFM 815 CFM 1015 CFM 1015 CFM 745 CFM | 4200 2315 3100 CURBS WITH VER ET WITH 1" R-7 (3- ED/LOUVERED HA E OUTSIDE AIR HC TER COMPRESSO I DRIVE EVAPOR/ RY-INSTALLED CO R, MECHANICAL AI S THAT DO NOT M PENALTY OF \$14/ RY MOUNTED MIC 5 COMPLIANT CL OF EQUIPMENT 1 JCTURE. FACHMENT HARD CTURAL DRAWING CURB MANUFACT NEERED ANALYS L NOT BE APPRO D 2"/4" FILTER RAC RY E-COATING OF CHEC MIN. COOLING FI 30% 30% 30% 30% 30% 30% 30% 30% | 725 550 525 TICAL DUCT 15 TONS) OR IL GUARDS (COD OR OPE R FOR FULL TOR FAN, A DNVENIENCE VD DDC CON IEET SPECIF TON FOR EV CROPROCES RB AND ATT O CURB. WARE STRE S FOR ROC URER IS ALS S AND THE E VED UNTIL A CK INTERAL CONDENSE OULE OW (%) | DOAS-2 DOAS-2 DOAS-2 DOAS-2 DOAS-2 DOAS-2 DOAS-2 DOAS-2 DOAS-2 CONNECTION, C 2" R-13 (16+ TO DR ANGLED CON NINGS. MODULATION O ND ECM MOTOR ELECTRICAL O ITRACTORS SHA IED EFFICIENCIE ERY 1/10 OF A P SOR CONTROLL ACHMENTS FRO NGTH. F SUBSTRATE E SO RESPONSIBL SOR CONTROLL ACHMENTS FRO NGTH. F SUBSTRATE E SO RESPONSIBL SOR CONTROLL ACHMENTS FRO DO THE UNIT WI ER COILS WITH N ELECTRICALV/P 208 V / 3 / 60 Hz 208 V / 3 / 60 Hz | 1.5 1.5 1.5 1.5 1.5 1.5 COPPER NS) DOU VDENSEF F CAPAC Q OR VFD UTLETS VITLETS ADL CORE SHALL OINT LOV E FOR PF STALLAT ATION LIS TH ONE S VINIMUM /H E Z </td <td>4 5 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 <td>49.4 44.7 27.1 27.1 36.3 36.3 RAP, EXV, TOTAL STRUCTION WITH STRUCTION WITH IRE GRILLES, 304 RATE LEAVING AIF FAN SPEED TO M STUS. SEE MECHA SION AND INSTAL SION AND INSTAL RFORMANCE PEN EDULED IEER BAS FACE WITH DDC. VEERED INSTALLA SHALL BE PERFORMANCE PEN PROVIDED ACCUF ANIZED FILTER FF 7 SALT SPRAY RA Image: Comparison of the structure of the structu</td><td>60 35 45 Y ENCLOSED F FOAM INSULAT STAINLESS STE TEMPERATURI EET STATIC PRINICAL ROOF PL ATION OF SEN ALTY, PAID TO ED ON A STAND RE. EQUIPMEN TION DRAWING RED SPECIFIC ATELY. AMES WITH ME TING. AT MANUFAC Titu Titu</td><td>208-3-60 208-3-60 208-3-60 208-3-60 208-3-60 208-3-60 AN MOTO ON, AND EL DRAIN CONTR SSURE S ANS FOR SORS AN WNER. WARD UN F OR CUF S FOR IT ALLY FO RV 8 FILT TURER 5 5 5 5 5 5 5 5 5 5 5 5 5</td><td>100 100 100 100 100 100 0RS, SS COIL C HINGED ACCES NPANS, GALVAI OL. SETPOINT. DUC LOCATIONS. D D SMOKE DETE IT OF THE SAME RB MANUFACTU TERS AND ONE TITUS MODEL DESV DESV</td><td>ASINGS A SS DOOR SS DOOR NIZED FIL T STATIC IV. 26 TO CTORS. E CAPACI JRER IS R STED ABC G AND PF SET OF 4 MODEL SIZE 08 08 08 12 08 08 08 12 08 08 12 08 08 08 12 08 08 08 12 08 08 08 12 08 08 08 12 08 08 08 12 08 08 08 12 08 08 08 12 08 08 08 12 08 08 08 08 12 08 08 08 12 08 08 08 08 12 08 08 08 12 08 08 08 08 12 08 08 08 08 08 08 08 08 08 08</td><td>13.7 16.5 16.1 AND FREI S. TER FRA PROVIDI TY AT AF ROJECT "MERV 1 ALL ALL ALL ALL ALL ALL ALL AL</td><td>95. 50. 72. EZE-STAT AMES, E-CO URE SENSO E WIRING A HRI CONDI SIBLE FOR SITE AND S 14 FILTERS</td><td>8 8 8 5 OPTIONS. OATED CON OATED CON OR BY RTU AND POWE TIONS. PROVIDING STAMPED A S. ADD 0.75 Image: Constraint of the second secon</td><td>75.0/63. 75.0/63. 75.0/63. NDENSER MFR. COOR FOR THE SENGINE NOT SEAL PRESSU</td><td>COILS COILS DRDIN IE OUT ERED I ERED I IRE DR IRE DR IRE DR</td></td> | 4 5 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 <td>49.4 44.7 27.1 27.1 36.3 36.3 RAP, EXV, TOTAL STRUCTION WITH STRUCTION WITH IRE GRILLES, 304 RATE LEAVING AIF FAN SPEED TO M STUS. SEE MECHA SION AND INSTAL SION AND INSTAL RFORMANCE PEN EDULED IEER BAS FACE WITH DDC. VEERED INSTALLA SHALL BE PERFORMANCE PEN PROVIDED ACCUF ANIZED FILTER FF 7 SALT SPRAY RA Image: Comparison of the structure of the structu</td> <td>60 35 45 Y ENCLOSED F FOAM INSULAT STAINLESS STE TEMPERATURI EET STATIC PRINICAL ROOF PL ATION OF SEN ALTY, PAID TO ED ON A STAND RE. EQUIPMEN TION DRAWING RED SPECIFIC ATELY. AMES WITH ME TING. AT MANUFAC Titu Titu</td> <td>208-3-60 208-3-60 208-3-60 208-3-60 208-3-60 208-3-60 AN MOTO ON, AND EL DRAIN CONTR SSURE S ANS FOR SORS AN WNER. WARD UN F OR CUF S FOR IT ALLY FO RV 8 FILT TURER 5 5 5 5 5 5 5 5 5 5 5 5 5</td> <td>100 100 100 100 100 100 0RS, SS COIL C HINGED ACCES NPANS, GALVAI OL. SETPOINT. DUC LOCATIONS. D D SMOKE DETE IT OF THE SAME RB MANUFACTU TERS AND ONE TITUS MODEL DESV DESV</td> <td>ASINGS A SS DOOR SS DOOR NIZED FIL T STATIC IV. 26 TO CTORS. E CAPACI JRER IS R STED ABC G AND PF SET OF 4 MODEL SIZE 08 08 08 12 08 08 08 12 08 08 12 08 08 08 12 08 08 08 12 08 08 08 12 08 08 08 12 08 08 08 12 08 08 08 12 08 08 08 12 08 08 08 12 08 08 08 08 12 08 08 08 12 08 08 08 08 12 08 08 08 12 08 08 08 08 12 08 08 08 08 08 08 08 08 08 08</td> <td>13.7 16.5 16.1 AND FREI S. TER FRA PROVIDI TY AT AF ROJECT "MERV 1 ALL ALL ALL ALL ALL ALL ALL AL</td> <td>95. 50. 72. EZE-STAT AMES, E-CO URE SENSO E WIRING A HRI CONDI SIBLE FOR SITE AND S 14 FILTERS</td> <td>8 8 8 5 OPTIONS. OATED CON OATED CON OR BY RTU AND POWE TIONS. PROVIDING STAMPED A S. ADD 0.75 Image: Constraint of the second secon</td> <td>75.0/63. 75.0/63. 75.0/63. NDENSER MFR. COOR FOR THE SENGINE NOT SEAL PRESSU</td> <td>COILS COILS DRDIN IE OUT ERED I ERED I IRE DR IRE DR IRE DR</td> | 49.4 44.7 27.1 27.1 36.3 36.3 RAP, EXV, TOTAL STRUCTION WITH STRUCTION WITH IRE GRILLES, 304 RATE LEAVING AIF FAN SPEED TO M STUS. SEE MECHA SION AND INSTAL SION AND INSTAL RFORMANCE PEN EDULED IEER BAS FACE WITH DDC. VEERED INSTALLA SHALL BE PERFORMANCE PEN PROVIDED ACCUF ANIZED FILTER FF 7 SALT SPRAY RA Image: Comparison of the structure of the structu | 60 35 45 Y ENCLOSED F FOAM INSULAT STAINLESS STE TEMPERATURI EET STATIC PRINICAL ROOF PL ATION OF SEN ALTY, PAID TO ED ON A STAND RE. EQUIPMEN TION DRAWING RED SPECIFIC ATELY. AMES WITH ME TING. AT MANUFAC Titu Titu | 208-3-60 208-3-60 208-3-60 208-3-60 208-3-60 208-3-60 AN MOTO ON, AND EL DRAIN CONTR SSURE S ANS FOR SORS AN WNER. WARD UN F OR CUF S FOR IT ALLY FO RV 8 FILT TURER 5 5 5 5 5 5 5 5 5 5 5 5 5 | 100 100 100 100 100 100 0RS, SS COIL C HINGED ACCES NPANS, GALVAI OL. SETPOINT. DUC LOCATIONS. D D SMOKE DETE IT OF THE SAME RB MANUFACTU TERS AND ONE TITUS MODEL DESV | ASINGS A SS DOOR SS DOOR NIZED FIL T STATIC IV. 26 TO CTORS. E CAPACI JRER IS R STED ABC G AND PF SET OF 4 MODEL SIZE 08 08 08 12 08 08 08 12 08 08 12 08 08 08 12 08 08 08 12 08 08 08 12 08 08 08 12 08 08 08 12 08 08 08 12 08 08 08 12 08 08 08 12 08 08 08 08 12 08 08 08 12 08 08 08 08 12 08 08 08 12 08 08 08 08 12 08 08 08 08 08 08 08 08 08 08 | 13.7 16.5 16.1 AND FREI S. TER FRA PROVIDI TY AT AF ROJECT "MERV 1 ALL ALL ALL ALL ALL ALL ALL AL | 95. 50. 72. EZE-STAT AMES, E-CO URE SENSO E WIRING A HRI CONDI SIBLE FOR SITE AND S 14 FILTERS | 8 8 8 5 OPTIONS. OATED CON OATED CON OR BY RTU AND POWE TIONS. PROVIDING STAMPED A S. ADD 0.75 Image: Constraint of the second secon | 75.0/63. 75.0/63. 75.0/63. NDENSER MFR. COOR FOR THE SENGINE NOT SEAL PRESSU | COILS COILS DRDIN IE OUT ERED I ERED I IRE DR IRE DR IRE DR |
| | TU-3 TU-4 TU-5 1. 2. 3. 4. 5. 6. 7. 8. 9. 10. 11. 12. 13. 14. Mark MAV-1-1 /AV-1-2 /AV-1-3 /AV-1-4 /AV-1-5 /AV-1-6 /AV-1-7 /AV-2-1 /AV-2-2 /AV-2-3 /AV-2-4 /AV-2-5 /AV-3-1 | 10 5 7 PROVIDE ROOF OPROVIDE CABINE PROVIDE CABINE PROVIDE INVERT PROVIDE DIRECT PROVIDE DIRECT PROVIDE DIRECT PROVIDE DIRECT PROVIDE INVERT PROVIDE DIRECT PROVIDE INVERT PROVIDE FACTOO EQUIPMENT MFR APPROVED MFRS PERFORMANCE IF PROVIDE FACTOO PROVIDE FACTOO | 4200 2315 3100 CURBS WITH VER ET WITH 1" R-7 (3- ED/LOUVERED HA E OUTSIDE AIR HO FER COMPRESSO I DRIVE EVAPORA RY-INSTALLED CO R, MECHANICAL AI S THAT DO NOT M PENALTY OF \$14/ RY MOUNTED MIC 5 COMPLIANT CL OF EQUIPMENT I JCTURE. IACHMENT HARD CTURAL DRAWING CURB MANUFACT NEERED ANALYS L NOT BE APPRO D 2"/4" FILTER RAC RY E-COATING O CURB MANUFACT NEERED ANALYS L NOT BE APPRO D 2"/4" FILTER RAC RY E-COATING O CHEC MIN. COOLING FI 30% 30% 30% 30% 30% 30% 30% 30% | 725 550 525 TICAL DUCT 15 TONS) OR IL GUARDS (DOD OR OPE R FOR FULL ATOR FAN, A DNVENIENCE ND DDC CON IEET SPECIF TON FOR EV CROPROCES RB AND ATT O CURB. WARE STRE SS FOR ROC URER IS ALS S AND THE F VED UNTIL A CK INTERAL CONDENSE OULE OW (%) F COW | DOAS-2 DO | 1.5 1.5 1.5 1.5 1.5 1.5 1.5 COPPER NS) DOU VDENSEF F CAPAC 2 OR VFD UTLETS ALL COOF ES SHALI OINT LO' ER, AND DM UNIT DETAILS. E FOR PF STALLAT ATION LIS TH ONE S MINIMUM /H E Z | 4 4 <td>49.4 44.7 27.1 27.1 36.3 36.3 RAP, EXV, TOTAL STRUCTION WITH IRE GRILLES, 304 ATE LEAVING AIF FAN SPEED TO M STUS. SEE MECHASION AND INSTAL SION AND INSTAL RFORMANCE PEN EDULED IEER BAS FACE WITH DDC. URB TO STRUCTUR VEERED INSTALLA SHALL BE PERFORMATION PROVIDED ACCUF ANIZED FILTER FF 7 SALT SPRAY RAY 2 2 3 3 1 2 3 3 2 2 3 3 3 2 3 3 3 2 3 3 3</td> <td>60 35 45 AY ENCLOSED F FOAM INSULAT STAINLESS STE TEMPERATURI EET STATIC PRINICAL ROOF PL ATION OF SEN ALTY, PAID TO ED ON A STAND RE. EQUIPMEN TION DRAWING RED SPECIFIC ATELY. AMES WITH ME TING. AT MANUFAC Titu Titu</td> <td>208-3-60 208-3-</td> <td>100 100 100 100 100 00 01000 01000 01000 01000 01000 01000 01000 01000 01000 01000 01000 01000</td> <td>ASINGS A SS DOOR: NIZED FIL T STATIC IV. 26 TO CTORS. E CAPACI JRER IS R STED ABC G AND PF SET OF 4 MODEL SIZE 08 08 08 12 08 08 12 08 08 14 14 12 14 12 08 16 16 16</td> <td>13.7 13.7 16.5 16.1 IND FREI S. TER FRA PROVIDI TY AT AF RESPONS OVE. ROJECT "MERV 1 ALL ALL ALL ALL ALL ALL ALL AL</td> <td>95. 50. 72. EZE-STAT AMES, E-CO URE SENSO E WIRING A HRI CONDI SIBLE FOR SITE AND S 14 FILTERS</td> <td>8 8 8 5 OPTIONS. OATED CON OATED CON OR BY RTU AND POWE TIONS. PROVIDING STAMPED A S. ADD 0.75 Image: Constraint of the second secon</td> <td>75.0/63. 75.0/63. 75.0/63. NDENSER MFR. COUR FOR THE ENGINE NOT SEAL "PRESSL MAR AND SEAL "PRESSL MAR ACCL NOT E 1. 2. 3. 4. 5. 6. 7.</td> <td>COILS COILS</td> | 49.4 44.7 27.1 27.1 36.3 36.3 RAP, EXV, TOTAL STRUCTION WITH IRE GRILLES, 304 ATE LEAVING AIF FAN SPEED TO M STUS. SEE MECHASION AND INSTAL SION AND INSTAL RFORMANCE PEN EDULED IEER BAS FACE WITH DDC. URB TO STRUCTUR VEERED INSTALLA SHALL BE PERFORMATION PROVIDED ACCUF ANIZED FILTER FF 7 SALT SPRAY RAY 2 2 3 3 1 2 3 3 2 2 3 3 3 2 3 3 3 2 3 3 3 | 60 35 45 AY ENCLOSED F FOAM INSULAT STAINLESS STE TEMPERATURI EET STATIC PRINICAL ROOF PL ATION OF SEN ALTY, PAID TO ED ON A STAND RE. EQUIPMEN TION DRAWING RED SPECIFIC ATELY. AMES WITH ME TING. AT MANUFAC Titu | 208-3-60 208-3- | 100 100 100 100 100 00 01000 01000 01000 01000 01000 01000 01000 01000 01000 01000 01000 01000 | ASINGS A SS DOOR: NIZED FIL T STATIC IV. 26 TO CTORS. E CAPACI JRER IS R STED ABC G AND PF SET OF 4 MODEL SIZE 08 08 08 12 08 08 12 08 08 14 14 12 14 12 08 16 16 16 | 13.7 13.7 16.5 16.1 IND FREI S. TER FRA PROVIDI TY AT AF RESPONS OVE. ROJECT "MERV 1 ALL ALL ALL ALL ALL ALL ALL AL | 95. 50. 72. EZE-STAT AMES, E-CO URE SENSO E WIRING A HRI CONDI SIBLE FOR SITE AND S 14 FILTERS | 8 8 8 5 OPTIONS. OATED CON OATED CON OR BY RTU AND POWE TIONS. PROVIDING STAMPED A S. ADD 0.75 Image: Constraint of the second secon | 75.0/63. 75.0/63. 75.0/63. NDENSER MFR. COUR FOR THE ENGINE NOT SEAL "PRESSL MAR AND SEAL "PRESSL MAR ACCL NOT E 1. 2. 3. 4. 5. 6. 7. | COILS |
| | TU-3 TU-4 TU-5 1. 2. 3. 4. 5. 6. 7. 8. 9. 10. 11. 11. 12. 13. 14. 14. 14. 14. 14. 14. 14. 14. 14. 14 | 10 5 7 PROVIDE ROOF OPROVIDE CABINE PROVIDE LOODE DO NOT PROVIDE PROVIDE INVERT PROVIDE DIRECT PROVIDE DIRECT PROVIDE DIRECT PROVIDE DIRECT PROVIDE INVERT PROVIDE DIRECT PROVIDE INVERT PROVIDE FACTOO EQUIPMENT MFR APPROVED MFRS PERFORMANCE IP PROVIDE FACTOO PROVIDE FACTOO PROVIDE FACTOO PROVIDE TO STRUE 3) CURB AND ATT REFER TO STRUE BOTH, THE ENGIN SUBMITTALS WIL PROVIDE COMBO PROVIDE FACTOO VIDE FACTOO PROVIDE FACTOO PROVIDE FACTOO VIDE FACTOO PROVIDE FACTOO Actual Supply Air Flow 300 CFM 3 | 4200 2315 3100 CURBS WITH VER ET WITH 1" R-7 (3- ED/LOUVERED HA E OUTSIDE AIR HO FER COMPRESSO I DRIVE EVAPOR/ RY-INSTALLED CO RY-INSTALLED CO RY-INSTALLED CO RY INSTALLED CO RY HOUNTED MIC IS COMPLIANT CL OF EQUIPMENT TO JCTURE. TACHMENT HARD CTURAL DRAWING CURB MANUFACT NEERED ANALYSI L NOT BE APPRO D 2"/4" FILTER RAC RY E-COATING O CHEC MIN. COOLING FI 30% 30% 30% 30% 30% 30% 30% 30% | 725 550 525 TICAL DUCT 15 TONS) OR IL GUARDS (DOD OR OPE R FOR FULL ATOR FAN, A DNVENIENCE ND DDC CON IEET SPECIF TON FOR EV CROPROCES RB AND ATT O CURB. WARE STRE SS FOR ROC URER IS ALS S AND THE F VED UNTIL A CK INTERAL CONDENSE DULE OW (%) | DOAS-2 DOAS-2 DOAS-2 DOAS-2 DOAS-2 DOAS-2 DOAS-2 DOAS-2 CONNECTION, C 2" R-13 (16+ TO DR ANGLED CON ND ECM MOTOR ELECTRICAL O ITRACTORS SHA IED EFFICIENCIE ERY 1/10 OF A P SOR CONTROLL ACHMENTS FRC NGTH. F SUBSTRATE ID SOR CONTROLL ACHMENTS FRC NGTH. F SUBSTRATE ID SOR CONTROLL ACHMENTS FRC NGTH. F SUBSTRATE ID SOR CONTROLL ACHMENTS FRC NGTH. F SUBSTRATE ID SOR CONTROLL ACHMENTS FRC NGTH. ELECTRICALV/P 208 V / 3 / 60 Hz 208 V / | 1.5 1.5 1.5 1.5 1.5 1.5 1.5 1.5 1.5 COPPER NS) DOU VIDENSEF F CAPAC 2 OR VFD UTLETS ALL COOF ES SHALL OINT LOV DETAILS. E FOR PF STALLAT ATION LIS TH ONE S MINIMUM /H Z | 4 4 <td>49.4 44.7 27.1 27.1 36.3 36.3 RAP, EXV, TOTAL STRUCTION WITH IRE GRILLES, 304 ATE LEAVING AIF FAN SPEED TO M SEE MECHA SION AND INSTAL RFORMANCE PEN EDULED IEER BAS FACE WITH DDC. URB TO STRUCTUR NEERED INSTALL/ SHALL BE PERFOR PROVIDED ACCUF ANIZED FILTER FF 7 SALT SPRAY R/ 2 2 3 3 1 2 3 3 3 2 3 3 3 2 3 3 3 2 3 3 3 2 3 3 3 3 3 2 3 3 3 2 3 3 3 3 3 2 3 3 3 2 3 3 3</td> <td>60 35 45 AY ENCLOSED F FOAM INSULAT STAINLESS STE TEMPERATURI EET STATIC PRINICAL ROOF PL ATION OF SEN ALTY, PAID TO GED ON A STAND RE. EQUIPMEN TION DRAWING RE. EQUIPMEN ATELY. AMES WITH ME TING. AT MANUFAC Titu Titu <</td> <td>208-3-60 208-3-</td> <td>100 100 100 100 100 00 01000 01000 01000 01000 01000 01000 01000 01000 01000 01000 01000 01000</td> <td>ASINGS A SS DOOR: NIZED FIL T STATIC IV. 26 TO CTORS. E CAPACI JRER IS R STED ABC G AND PF SET OF 4 MODEL SIZE 08 08 08 12 08 08 12 08 08 12 08 08 12 08 08 12 08 08 12 08 08 08 12 08 08 08 08 12 08 08 08 08 12 08 08 08 08 12 08 08 08 08 08 08 08 08 08 08</td> <td>13.7 13.7 16.5 16.1 IND FREI S. TER FRA PROVIDI TY AT AF RESPONS OVE. ROJECT "MERV 1 MERV 1 MERV 1 ALL ALL ALL ALL ALL ALL ALL AL</td> <td>95. 50. 72. EZE-STAT AMES, E-CO URE SENSO E WIRING / HRI CONDI SIBLE FOR SITE AND : 14 FILTERS</td> <td>8 8 8 5 OPTIONS. OATED CON OATED CON OR BY RTU AND POWE TIONS. PROVIDING STAMPED A S. ADD 0.75 Image: Constraint of the second secon</td> <td>75.0/63. 75.0/63. 75.0/63. NDENSER MFR. COOR FOR THE SENGINE NOTE NOTE 1. 2. 3. 4. 5. 6. 7. 8.</td> <td>COILS COILS</td> | 49.4 44.7 27.1 27.1 36.3 36.3 RAP, EXV, TOTAL STRUCTION WITH IRE GRILLES, 304 ATE LEAVING AIF FAN SPEED TO M SEE MECHA SION AND INSTAL RFORMANCE PEN EDULED IEER BAS FACE WITH DDC. URB TO STRUCTUR NEERED INSTALL/ SHALL BE PERFOR PROVIDED ACCUF ANIZED FILTER FF 7 SALT SPRAY R/ 2 2 3 3 1 2 3 3 3 2 3 3 3 2 3 3 3 2 3 3 3 2 3 3 3 3 3 2 3 3 3 2 3 3 3 3 3 2 3 3 3 2 3 3 3 | 60 35 45 AY ENCLOSED F FOAM INSULAT STAINLESS STE TEMPERATURI EET STATIC PRINICAL ROOF PL ATION OF SEN ALTY, PAID TO GED ON A STAND RE. EQUIPMEN TION DRAWING RE. EQUIPMEN ATELY. AMES WITH ME TING. AT MANUFAC Titu Titu < | 208-3-60 208-3- | 100 100 100 100 100 00 01000 01000 01000 01000 01000 01000 01000 01000 01000 01000 01000 01000 | ASINGS A SS DOOR: NIZED FIL T STATIC IV. 26 TO CTORS. E CAPACI JRER IS R STED ABC G AND PF SET OF 4 MODEL SIZE 08 08 08 12 08 08 12 08 08 12 08 08 12 08 08 12 08 08 12 08 08 08 12 08 08 08 08 12 08 08 08 08 12 08 08 08 08 12 08 08 08 08 08 08 08 08 08 08 | 13.7 13.7 16.5 16.1 IND FREI S. TER FRA PROVIDI TY AT AF RESPONS OVE. ROJECT "MERV 1 MERV 1 MERV 1 ALL ALL ALL ALL ALL ALL ALL AL | 95. 50. 72. EZE-STAT AMES, E-CO URE SENSO E WIRING / HRI CONDI SIBLE FOR SITE AND : 14 FILTERS | 8 8 8 5 OPTIONS. OATED CON OATED CON OR BY RTU AND POWE TIONS. PROVIDING STAMPED A S. ADD 0.75 Image: Constraint of the second secon | 75.0/63. 75.0/63. 75.0/63. NDENSER MFR. COOR FOR THE SENGINE NOTE NOTE 1. 2. 3. 4. 5. 6. 7. 8. | COILS |
| | TU-3 TU-4 TU-5 1. 2. 3. 4. 5. 6. 7. 8. 9. 10. 11. 11. 12. 13. 14. 14. 14. 14. 14. 14. 14. 14. 14. 14 | 10 5 7 PROVIDE ROOF OPROVIDE CABINE PROVIDE HOODE DO NOT PROVIDE PROVIDE INVERT PROVIDE DIRECT PROVIDE DIRECT PROVIDE INVERT PROVIDE DIRECTO PROVIDE INVERT PROVIDE FACTOR EQUIPMENT MFR APPROVED MFRS PERFORMANCE IP PROVIDE FACTOR PROVIDE FACTOR PROVIDE FACTOR BOTH, THE ENGIN SUBMITTALS WIL PROVIDE COMBOR PROVIDE FACTOR OX S Actual Supply Air Flow 430 CFM 350 CFM 340 CFM 500 CFM | 4200 2315 3100 CURBS WITH VER ET WITH 1" R-7 (3- ED/LOUVERED HA E OUTSIDE AIR HG TER COMPRESSO I DRIVE EVAPORA RY-INSTALLED CO R, MECHANICAL AI S THAT DO NOT M PENALTY OF \$14/ RY MOUNTED MIC 5 COMPLIANT CL OF EQUIPMENT T JCTURE. IACHMENT HARD CTURAL DRAWING CURB MANUFACT NEERED ANALYS L NOT BE APPRO D 2"/4" FILTER RAG RY E-COATING OF CHEC MIN. COOLING FI 30% 30% 30% 30% 30% 30% 30% 30% | 725 550 525 TICAL DUCT 15 TONS) OR IL GUARDS (C COD OR OPE R FOR FULL TOR FAN, A DNVENIENCE ND DDC CON IEET SPECIF TON FOR EV CROPROCES RB AND ATT O CURB. WARE STRE BS FOR ROC URER IS ALS S AND THE E VED UNTIL A CONDENSE OULE OULE OW (%) F OULE OW (%) F OULE | DOAS-2 | 1.5 1.5 1.5 1.5 1.5 1.5 1.5 1.5 1.5 1.5 1.5 COPPER NS) DOU VDENSEF F CAPAC COR VFD UTLETS ALL COOF ES SHALL OINT LOV EF CAP PF STALLAT ATION LIS TH ONE S MINIMUM /H Z | 4 4 <td>49.4 44.7 27.1 27.1 36.3 36.3 RAP, EXV, TOTAL STRUCTION WITH REGRILLES, 304 STRUCTION WITH RECOMMANCE PENE STRUCTION EDULED IEER BAS FACE WITH DDC. URB TO STRUCTUR STRUCTION NEERED INSTALL STRUCTION SHALL BE PERFOR STRUCTION PROVIDED ACCUPANIZED FILTER FF TO SALT SPRAY R 2 3 3 1 2 3 3 2 3 3 2 3 3 3 2 3 3 3 2 3 3 3 2 3 3 3 2 3 3 3 2 3 3 3 <t< td=""><td>60 35 45 .Y ENCLOSED F FOAM INSULAT STAINLESS STE TEMPERATURI EET STATIC PRINICAL ROOF PL ATION OF SEN ALTY, PAID TO 0 ED ON A STANI RE. EQUIPMEN TION DRAWING RMED SPECIFIC ATELY. AMES WITH ME TING. AT MANUFAC Titu Titu</td><td>208-3-60 208-3-</td><td>100 100 100 100 100 00 00 000</td><td>11 5 8 ASINGS A SS DOOR: NIZED FIL T STATIC IV. 26 TO IV. 26 TO CTORS. E CAPACI JRER IS R STED ABG G AND PF SET OF 4 08 08 08 08 12 08 12 08 14 12 08 14 12 08 14 12 08 12 08 12 03 14 12 03 16 16 08 16 16 16 16 16 16 16 16</td><td>13.7 16.5 16.1 AND FREI S. TER FRA PROVIDI TY AT AH RESPONS OVE. ROJECT : "MERV 1 ALL ALL ALL ALL ALL ALL ALL AL</td><td>95. 50. 72. EZE-STAT AMES, E-CO URE SENSO E WIRING / HRI CONDI SIBLE FOR SITE AND S 14 FILTERS</td><td>8 8 8 5 OPTIONS. OATED CON OATED CON OR BY RTU AND POWE TIONS. PROVIDING STAMPED A S. ADD 0.75 Image: Constraint of the second secon</td><td>75.0/63. 75.0/63. 75.0/63. NDENSER MFR. COOR FOR TH SENGINE ND SEAL PRESSU MAR ACCU NOTE 1. 2. 3. 4. 5. 6. 7. 8.</td><td>COILS COILS DRDIN ERED I ERED I ERED I IRE DR SF K J-1 SS:</td></t<></td> | 49.4 44.7 27.1 27.1 36.3 36.3 RAP, EXV, TOTAL STRUCTION WITH REGRILLES, 304 STRUCTION WITH RECOMMANCE PENE STRUCTION EDULED IEER BAS FACE WITH DDC. URB TO STRUCTUR STRUCTION NEERED INSTALL STRUCTION SHALL BE PERFOR STRUCTION PROVIDED ACCUPANIZED FILTER FF TO SALT SPRAY R 2 3 3 1 2 3 3 2 3 3 2 3 3 3 2 3 3 3 2 3 3 3 2 3 3 3 2 3 3 3 2 3 3 3 <t< td=""><td>60 35 45 .Y ENCLOSED F FOAM INSULAT STAINLESS STE TEMPERATURI EET STATIC PRINICAL ROOF PL ATION OF SEN ALTY, PAID TO 0 ED ON A STANI RE. EQUIPMEN TION DRAWING RMED SPECIFIC ATELY. AMES WITH ME TING. AT MANUFAC Titu Titu</td><td>208-3-60 208-3-</td><td>100 100 100 100 100 00 00 000</td><td>11 5 8 ASINGS A SS DOOR: NIZED FIL T STATIC IV. 26 TO IV. 26 TO CTORS. E CAPACI JRER IS R STED ABG G AND PF SET OF 4 08 08 08 08 12 08 12 08 14 12 08 14 12 08 14 12 08 12 08 12 03 14 12 03 16 16 08 16 16 16 16 16 16 16 16</td><td>13.7 16.5 16.1 AND FREI S. TER FRA PROVIDI TY AT AH RESPONS OVE. ROJECT : "MERV 1 ALL ALL ALL ALL ALL ALL ALL AL</td><td>95. 50. 72. EZE-STAT AMES, E-CO URE SENSO E WIRING / HRI CONDI SIBLE FOR SITE AND S 14 FILTERS</td><td>8 8 8 5 OPTIONS. OATED CON OATED CON OR BY RTU AND POWE TIONS. PROVIDING STAMPED A S. ADD 0.75 Image: Constraint of the second secon</td><td>75.0/63. 75.0/63. 75.0/63. NDENSER MFR. COOR FOR TH SENGINE ND SEAL PRESSU MAR ACCU NOTE 1. 2. 3. 4. 5. 6. 7. 8.</td><td>COILS COILS DRDIN ERED I ERED I ERED I IRE DR SF K J-1 SS:</td></t<> | 60 35 45 .Y ENCLOSED F FOAM INSULAT STAINLESS STE TEMPERATURI EET STATIC PRINICAL ROOF PL ATION OF SEN ALTY, PAID TO 0 ED ON A STANI RE. EQUIPMEN TION DRAWING RMED SPECIFIC ATELY. AMES WITH ME TING. AT MANUFAC Titu | 208-3-60 208-3- | 100 100 100 100 100 00 00 000 | 11 5 8 ASINGS A SS DOOR: NIZED FIL T STATIC IV. 26 TO IV. 26 TO CTORS. E CAPACI JRER IS R STED ABG G AND PF SET OF 4 08 08 08 08 12 08 12 08 14 12 08 14 12 08 14 12 08 12 08 12 03 14 12 03 16 16 08 16 16 16 16 16 16 16 16 | 13.7 16.5 16.1 AND FREI S. TER FRA PROVIDI TY AT AH RESPONS OVE. ROJECT : "MERV 1 ALL ALL ALL ALL ALL ALL ALL AL | 95. 50. 72. EZE-STAT AMES, E-CO URE SENSO E WIRING / HRI CONDI SIBLE FOR SITE AND S 14 FILTERS | 8 8 8 5 OPTIONS. OATED CON OATED CON OR BY RTU AND POWE TIONS. PROVIDING STAMPED A S. ADD 0.75 Image: Constraint of the second secon | 75.0/63. 75.0/63. 75.0/63. NDENSER MFR. COOR FOR TH SENGINE ND SEAL PRESSU MAR ACCU NOTE 1. 2. 3. 4. 5. 6. 7. 8. | COILS COILS DRDIN ERED I ERED I ERED I IRE DR SF K J-1 SS: |
| | TU-3 TU-4 TU-5 TU-5 1. 2. 3. 4. 5. 6. 7. 8. 9. 10. 11. 11. 12. 13. 14. 14. 12. 13. 14. 14. 14. 14. 14. 14. 14. 14. 14. 14 | 10 5 7 PROVIDE ROOF OPROVIDE CABINE PROVIDE HOODE DO NOT PROVIDE PROVIDE INVERT PROVIDE DIRECT PROVIDE INVERT PROVIDE DIRECT PROVIDE INVERT PROVIDE INVERT PROVIDE FACTO EQUIPMENT MFR APPROVED MFRS PERFORMANCE IF PROVIDE FACTO OX S Actual Supply Air Flow 430 CFM 885 CFM 745 CFM 300 CFM 350 CFM 815 CFM 350 CFM 815 CFM 100 CFM 690 CFM 1015 CFM 75 CFM 340 CFM 690 CFM 1015 CFM 75 CFM 75 CFM | 4200 2315 3100 CURBS WITH VER T WITH 1" R-7 (3- ED/LOUVERED HA E OUTSIDE AIR HC TER COMPRESSO I DRIVE EVAPORA RY-INSTALLED CO R, MECHANICAL AI S THAT DO NOT M PENALTY OF \$14/ RY MOUNTED MIC 5 COMPLIANT CL OF EQUIPMENT 1 JCTURE. FACHMENT HARD CTURAL DRAWING CURB MANUFACT NEERED ANALYS L NOT BE APPRO D 2"/4" FILTER RAC RY E-COATING OF CHEC MIN. COOLING FI 30% 30% 30% 30% 30% 30% 30% 30% | 725 550 525 TICAL DUCT 15 TONS) OR IL GUARDS (COD OR OPE R FOR FULL TOR FAN, A DNVENIENCE VD DDC CON IEET SPECIF TON FOR EV CROPROCES RB AND ATT O CURB. WARE STRE SS FOR ROC URER IS ALS S AND THE E VED UNTIL A CK INTERAL CONDENSE OULE OW (%) E OULE | DOAS-2 DO | 1.5 1.5 1.5 1.5 1.5 1.5 1.5 1.5 1.5 COPPER NS) DOU VDENSEF F CAPAC COR VFD UTLETS ALL COOF ES SHALL OINT LOU DM UNIT DETAILS. E FOR PF STALLAT ATION LIS TH ONE S MINIMUM /H Z < | 4 4 <td>49.4 44.7 27.1 27.1 36.3 36.3 RAP, EXV, TOTAL STRUCTION WITH IRE GRILLES, 304 RAP, EXV, TOTAL STEPED TO M STEPS EDULED IEER BAS FACE WITH DDC. URB TO STRUCTU VEERED INSTALLA STEPS 2 A A A STEPS 2 2 3 3 2 3 3 3 2 3 3 3 2 3 3 3 2 2 <t< td=""><td>60 35 45 .Y ENCLOSED F FOAM INSULAT STAINLESS STE TEMPERATURI EET STATIC PRINICAL ROOF PL ATION OF SEN ALTY, PAID TO 0 ED ON A STANI RE. EQUIPMEN TION DRAWING RMED SPECIFIC AMES WITH ME TING. AT MANUFAC Titu Titu</td><td>208-3-60 208-3-</td><td>100 100 100 100 100 100 00 DRS, SS COIL C HINGED ACCES NPANS, GALVAI OL. SETPOINT. DUC LOCATIONS. D D SMOKE DETE IT OF THE SAME RB MANUFACTU TERS AND ONE TITUS MODEL DESV DESV</td><td>11 5 8 ASINGS A SS DOOR SS DOOR NIZED FIL T STATIC IV. 26 TO CTORS. E CAPACI JRER IS R STED ABG G AND PF SET OF 4 MODEL SIZE 08 08 08 08 08 08 12 08 14 12 08 12 08 12 08 12 08 12 14 12 14 12 14</td><td>13.7 16.5 16.1 AND FREI S. TER FRA PROVIDI TY AT AF RESPONS OVE. ROJECT "MERV 1 ALL ALL ALL ALL ALL ALL ALL AL</td><td>95. 50. 72. EZE-STAT AMES, E-CO URE SENSO E WIRING , HRI CONDI SIBLE FOR SITE AND S 14 FILTERS</td><td>8 8 8 5 OPTIONS. OATED CON OATED CON OR BY RTU AND POWE TIONS. PROVIDING STAMPED A S. ADD 0.75 Image: Constraint of the second secon</td><td>75.0/63. 75.0/63. 75.0/63. NDENSER MFR. COR R FOR TH S ENGINE ND SEAL " PRESSU MAR AND SEAL " PRESSU MAR ACCL NOTE 1. 2. 3. 4. 5. 6. 7. 8.</td><td></td></t<></td> | 49.4 44.7 27.1 27.1 36.3 36.3 RAP, EXV, TOTAL STRUCTION WITH IRE GRILLES, 304 RAP, EXV, TOTAL STEPED TO M STEPS EDULED IEER BAS FACE WITH DDC. URB TO STRUCTU VEERED INSTALLA STEPS 2 A A A STEPS 2 2 3 3 2 3 3 3 2 3 3 3 2 3 3 3 2 2 <t< td=""><td>60 35 45 .Y ENCLOSED F FOAM INSULAT STAINLESS STE TEMPERATURI EET STATIC PRINICAL ROOF PL ATION OF SEN ALTY, PAID TO 0 ED ON A STANI RE. EQUIPMEN TION DRAWING RMED SPECIFIC AMES WITH ME TING. AT MANUFAC Titu Titu</td><td>208-3-60 208-3-</td><td>100 100 100 100 100 100 00 DRS, SS COIL C HINGED ACCES NPANS, GALVAI OL. SETPOINT. DUC LOCATIONS. D D SMOKE DETE IT OF THE SAME RB MANUFACTU TERS AND ONE TITUS MODEL DESV DESV</td><td>11 5 8 ASINGS A SS DOOR SS DOOR NIZED FIL T STATIC IV. 26 TO CTORS. E CAPACI JRER IS R STED ABG G AND PF SET OF 4 MODEL SIZE 08 08 08 08 08 08 12 08 14 12 08 12 08 12 08 12 08 12 14 12 14 12 14</td><td>13.7 16.5 16.1 AND FREI S. TER FRA PROVIDI TY AT AF RESPONS OVE. ROJECT "MERV 1 ALL ALL ALL ALL ALL ALL ALL AL</td><td>95. 50. 72. EZE-STAT AMES, E-CO URE SENSO E WIRING , HRI CONDI SIBLE FOR SITE AND S 14 FILTERS</td><td>8 8 8 5 OPTIONS. OATED CON OATED CON OR BY RTU AND POWE TIONS. PROVIDING STAMPED A S. ADD 0.75 Image: Constraint of the second secon</td><td>75.0/63. 75.0/63. 75.0/63. NDENSER MFR. COR R FOR TH S ENGINE ND SEAL " PRESSU MAR AND SEAL " PRESSU MAR ACCL NOTE 1. 2. 3. 4. 5. 6. 7. 8.</td><td></td></t<> | 60 35 45 .Y ENCLOSED F FOAM INSULAT STAINLESS STE TEMPERATURI EET STATIC PRINICAL ROOF PL ATION OF SEN ALTY, PAID TO 0 ED ON A STANI RE. EQUIPMEN TION DRAWING RMED SPECIFIC AMES WITH ME TING. AT MANUFAC Titu | 208-3-60 208-3- | 100 100 100 100 100 100 00 DRS, SS COIL C HINGED ACCES NPANS, GALVAI OL. SETPOINT. DUC LOCATIONS. D D SMOKE DETE IT OF THE SAME RB MANUFACTU TERS AND ONE TITUS MODEL DESV | 11 5 8 ASINGS A SS DOOR SS DOOR NIZED FIL T STATIC IV. 26 TO CTORS. E CAPACI JRER IS R STED ABG G AND PF SET OF 4 MODEL SIZE 08 08 08 08 08 08 12 08 14 12 08 12 08 12 08 12 08 12 14 12 14 12 14 | 13.7 16.5 16.1 AND FREI S. TER FRA PROVIDI TY AT AF RESPONS OVE. ROJECT "MERV 1 ALL ALL ALL ALL ALL ALL ALL AL | 95. 50. 72. EZE-STAT AMES, E-CO URE SENSO E WIRING , HRI CONDI SIBLE FOR SITE AND S 14 FILTERS | 8 8 8 5 OPTIONS. OATED CON OATED CON OR BY RTU AND POWE TIONS. PROVIDING STAMPED A S. ADD 0.75 Image: Constraint of the second secon | 75.0/63. 75.0/63. 75.0/63. NDENSER MFR. COR R FOR TH S ENGINE ND SEAL " PRESSU MAR AND SEAL " PRESSU MAR ACCL NOTE 1. 2. 3. 4. 5. 6. 7. 8. | |
| | TU-3 TU-4 TU-5 TU-5 1. 2. 3. 4. 5. 6. 7. 8. 9. 10. 11. 11. 12. 13. 14. 14. 14. 14. 14. 14. 14. 14. 14. 14 | 10 5 7 PROVIDE ROOF OPROVIDE CABINE PROVIDE CABINE PROVIDE INVERT PROVIDE DIRECT PROVIDE INVERT PROVIDE DIRECT PROVIDE INVERT PROVIDE FACTO EQUIPMENT MFR APPROVED MFRS PERFORMANCE IF PROVIDE FACTO PROVIDE FACT | 4200 2315 3100 CURBS WITH VER ET WITH 1" R-7 (3- ED/LOUVERED HA E OUTSIDE AIR HO FER COMPRESSO I DRIVE EVAPOR/ RY-INSTALLED CO R, MECHANICAL AI S THAT DO NOT M PENALTY OF \$14/ RY MOUNTED MIC 5 COMPLIANT CL OF EQUIPMENT T JCTURE. IACHMENT HARD CTURAL DRAWING CURB MANUFACT NEERED ANALYS L NOT BE APPRO D 2"/4" FILTER RAG RY E-COATING O CHEC MIN. COOLING FI 30% 30% 30% 30% 30% 30% 30% 30% | 725 550 525 TICAL DUCT 15 TONS) OR 16 GUARDS O 200 OR OPE R FOR FULL TOR FAN, A DNVENIENCE 10 DDC CON 10 DDC CON 1 | DOAS-2 DOAS-2 DOAS-2 DOAS-2 DOAS-2 DOAS-2 DOAS-2 DOAS-2 CONNECTION, G 2" R-13 (16+ TO DR ANGLED CON NINGS. MODULATION O ND ECM MOTOR ELECTRICAL O ITRACTORS SHA IED EFFICIENCIE ERY 1/10 OF A P SOR CONTROLL ACHMENTS FROM NGTH. OF SUBSTRATE D SOR CONTROLL ACHMENTS FROM SOR CONTROLL ACOM / 3 / 60 Hz 208 V / 3 / 60 Hz | 1.5 1.5 1.5 1.5 1.5 1.5 1.5 COPPER NS) DOU VIDENSEF F CAPAC COR VFD UTLETS ALL COOF ES SHALL OINT LOV EF CAP AC OINT LOV DETAILS. E FOR PF STALLAT ATION LIS TH ONE S MINIMUM /H E Z <td>4 4 <td>49.4 44.7 27.1 27.1 36.3 36.3 RAP, EXV, TOTAL STRUCTION WITH IRE GRILLES, 304 ATE LEAVING AIF FAN SPEED TO M STRUCTION WITH IRE GRILLES, 304 ATE LEAVING AIF FAN SPEED TO M STRUCTION WITH REGRILLES, 304 ATE LEAVING AIF FAN SPEED TO M STRUCTION SION AND INSTAL RFORMANCE PEN EDULED IEER BAS FACE WITH DDC. URB TO STRUCTUR VEERED INSTALL/ SHALL BE PERFOR PROVIDED ACCUF ANIZED FILTER FF 7 7 SALT SPRAY R/ Image: Construction of the structure of the str</td><td>60 35 45 AY ENCLOSED F FOAM INSULAT STAINLESS STE TEMPERATURI EET STATIC PRINICAL ROOF PL ATION OF SEN ALTY, PAID TO ED ON A STAND RE. EQUIPMEN TION DRAWING RED SPECIFIC ATELY. AMES WITH ME TING. AT MANUFAC Titu Tit</td><td>208-3-60 208-3-</td><td>100 100 100 100 100 100 00 DRS, SS COIL C HINGED ACCES N PANS, GALVAI OL. SETPOINT. DUC LOCATIONS. D D SMOKE DETE IT OF THE SAME RB MANUFACTU THIS BUILDIN TERS AND ONE DESV DESV <t< td=""><td>11 5 8 ASINGS A SS DOOR: NIZED FIL T STATIC IV. 26 TO CTORS: E CAPACI JRER IS R STED ABC G AND PF SET OF 4 08 08 08 08 08 12 08 08 12 08 14 12 08 14 12 14 12 14 12 14 12 14 12 14 12 14 12 14 12 14 12 14 12 14 12 14 12 14 12</td><td>13.7 16.5 16.1 16.1 10.1</td><td>95. 50. 72. EZE-STAT AMES, E-CO URE SENSO E WIRING A HRI CONDI SIBLE FOR SITE AND 14 FILTERS</td><td>8 8 8 5 OPTIONS. OATED CON OR BY RTU AND POWE TIONS. PROVIDING STAMPED A S. ADD 0.75</td><td>75.0/63. 75.0/63. 75.0/63. NDENSER MFR. COUR FOR THE ENGINE NOTE NOTE 1. 2. 3. 4. 5. 6. 7. 8.</td><td></td></t<></td></td> | 4 4 <td>49.4 44.7 27.1 27.1 36.3 36.3 RAP, EXV, TOTAL STRUCTION WITH IRE GRILLES, 304 ATE LEAVING AIF FAN SPEED TO M STRUCTION WITH IRE GRILLES, 304 ATE LEAVING AIF FAN SPEED TO M STRUCTION WITH REGRILLES, 304 ATE LEAVING AIF FAN SPEED TO M STRUCTION SION AND INSTAL RFORMANCE PEN EDULED IEER BAS FACE WITH DDC. URB TO STRUCTUR VEERED INSTALL/ SHALL BE PERFOR PROVIDED ACCUF ANIZED FILTER FF 7 7 SALT SPRAY R/ Image: Construction of the structure of the str</td> <td>60 35 45 AY ENCLOSED F FOAM INSULAT STAINLESS STE TEMPERATURI EET STATIC PRINICAL ROOF PL ATION OF SEN ALTY, PAID TO ED ON A STAND RE. EQUIPMEN TION DRAWING RED SPECIFIC ATELY. AMES WITH ME TING. AT MANUFAC Titu Tit</td> <td>208-3-60 208-3-</td> <td>100 100 100 100 100 100 00 DRS, SS COIL C HINGED ACCES N PANS, GALVAI OL. SETPOINT. DUC LOCATIONS. D D SMOKE DETE IT OF THE SAME RB MANUFACTU THIS BUILDIN TERS AND ONE DESV DESV <t< td=""><td>11 5 8 ASINGS A SS DOOR: NIZED FIL T STATIC IV. 26 TO CTORS: E CAPACI JRER IS R STED ABC G AND PF SET OF 4 08 08 08 08 08 12 08 08 12 08 14 12 08 14 12 14 12 14 12 14 12 14 12 14 12 14 12 14 12 14 12 14 12 14 12 14 12 14 12</td><td>13.7 16.5 16.1 16.1 10.1</td><td>95. 50. 72. EZE-STAT AMES, E-CO URE SENSO E WIRING A HRI CONDI SIBLE FOR SITE AND 14 FILTERS</td><td>8 8 8 5 OPTIONS. OATED CON OR BY RTU AND POWE TIONS. PROVIDING STAMPED A S. ADD 0.75</td><td>75.0/63. 75.0/63. 75.0/63. NDENSER MFR. COUR FOR THE ENGINE NOTE NOTE 1. 2. 3. 4. 5. 6. 7. 8.</td><td></td></t<></td> | 49.4 44.7 27.1 27.1 36.3 36.3 RAP, EXV, TOTAL STRUCTION WITH IRE GRILLES, 304 ATE LEAVING AIF FAN SPEED TO M STRUCTION WITH IRE GRILLES, 304 ATE LEAVING AIF FAN SPEED TO M STRUCTION WITH REGRILLES, 304 ATE LEAVING AIF FAN SPEED TO M STRUCTION SION AND INSTAL RFORMANCE PEN EDULED IEER BAS FACE WITH DDC. URB TO STRUCTUR VEERED INSTALL/ SHALL BE PERFOR PROVIDED ACCUF ANIZED FILTER FF 7 7 SALT SPRAY R/ Image: Construction of the structure of the str | 60 35 45 AY ENCLOSED F FOAM INSULAT STAINLESS STE TEMPERATURI EET STATIC PRINICAL ROOF PL ATION OF SEN ALTY, PAID TO ED ON A STAND RE. EQUIPMEN TION DRAWING RED SPECIFIC ATELY. AMES WITH ME TING. AT MANUFAC Titu Tit | 208-3-60 208-3- | 100 100 100 100 100 100 00 DRS, SS COIL C HINGED ACCES N PANS, GALVAI OL. SETPOINT. DUC LOCATIONS. D D SMOKE DETE IT OF THE SAME RB MANUFACTU THIS BUILDIN TERS AND ONE DESV DESV <t< td=""><td>11 5 8 ASINGS A SS DOOR: NIZED FIL T STATIC IV. 26 TO CTORS: E CAPACI JRER IS R STED ABC G AND PF SET OF 4 08 08 08 08 08 12 08 08 12 08 14 12 08 14 12 14 12 14 12 14 12 14 12 14 12 14 12 14 12 14 12 14 12 14 12 14 12 14 12</td><td>13.7 16.5 16.1 16.1 10.1</td><td>95. 50. 72. EZE-STAT AMES, E-CO URE SENSO E WIRING A HRI CONDI SIBLE FOR SITE AND 14 FILTERS</td><td>8 8 8 5 OPTIONS. OATED CON OR BY RTU AND POWE TIONS. PROVIDING STAMPED A S. ADD 0.75</td><td>75.0/63. 75.0/63. 75.0/63. NDENSER MFR. COUR FOR THE ENGINE NOTE NOTE 1. 2. 3. 4. 5. 6. 7. 8.</td><td></td></t<> | 11 5 8 ASINGS A SS DOOR: NIZED FIL T STATIC IV. 26 TO CTORS: E CAPACI JRER IS R STED ABC G AND PF SET OF 4 08 08 08 08 08 12 08 08 12 08 14 12 08 14 12 14 12 14 12 14 12 14 12 14 12 14 12 14 12 14 12 14 12 14 12 14 12 14 12 | 13.7 16.5 16.1 16.1 10.1 | 95. 50. 72. EZE-STAT AMES, E-CO URE SENSO E WIRING A HRI CONDI SIBLE FOR SITE AND 14 FILTERS | 8 8 8 5 OPTIONS. OATED CON OR BY RTU AND POWE TIONS. PROVIDING STAMPED A S. ADD 0.75 | 75.0/63. 75.0/63. 75.0/63. NDENSER MFR. COUR FOR THE ENGINE NOTE NOTE 1. 2. 3. 4. 5. 6. 7. 8. | |
| | TU-3 TU-4 TU-5 TU-5 1. 2. 3. 4. 5. 6. 7. 8. 9. 10. 11. 11. 12. 13. 14. 14. 14. 14. 14. 14. 14. 14. 14. 14 | 10 5 7 PROVIDE ROOF OPROVIDE CABINE PROVIDE CABINE PROVIDE INVERT PROVIDE INVERT PROVIDE DIRECT PROVIDE INVERT PROVIDE DIRECT PROVIDE INVERT PROVIDE INVERT PROVIDE INVERT PROVIDE INVERT PROVIDE FACTOR PROVIDE FACTOR PROVIDE IBC 201 1) ATTACHMENT 2) CURB TO STRUCT BOTH, THE ENGING SUBMITTALS WILL PROVIDE FACTOR PROVIDE FACTOR PROVIDE COMBOR PROVIDE FACTOR OX S Actual Supply Air Flow 430 CFM 3300 CFM 375 CFM 300 CFM 375 CFM 370 CFM 450 C | 4200 2315 3100 CURBS WITH VER ET WITH 1" R-7 (3- ED/LOUVERED HA E OUTSIDE AIR HO FER COMPRESSO I DRIVE EVAPORA RY-INSTALLED CO R, MECHANICAL AI S THAT DO NOT M PENALTY OF \$14/ RY MOUNTED MIC IS COMPLIANT CL OF EQUIPMENT I JCTURE. TACHMENT HARD CTURAL DRAWING CURB MANUFACT NEERED ANALYS L NOT BE APPRO D 2"/4" FILTER RAC RY E-COATING O CHEC MIN. COOLING FI 30% 30% 30% 30% 30% 30% 30% 30% | 725 550 525 TICAL DUCT 15 TONS) OR IL GUARDS (DOD OR OPE) R FOR FULL ATOR FAN, A DNVENIENCE ND DDC CON IEET SPECIF TON FOR EV CROPROCES RB AND ATT O CURB. WARE STRE SS FOR ROC URER IS ALS S AND THE F VED UNTIL A CK INTERAL CONDENSE OW (%) I OW (%) I OW (%) I < | DOAS-2 DOAS-2 DOAS-2 DOAS-2 DOAS-2 DOAS-2 DOAS-2 DOAS-2 CONNECTION, G 2" R-13 (16+ TO DR ANGLED CON NINGS. MODULATION O ND ECM MOTOR ELECTRICAL O ITRACTORS SHA IED EFFICIENCIE ERY 1/10 OF A P SOR CONTROLL ACHMENTS FROM NGTH. OF SUBSTRATE D SOR CONTROLL ACHMENTS FROM SOR V / 3 / 60 Hz 208 V / 3 | 1.5 1.5 1.5 1.5 1.5 1.5 1.5 1.5 COPPER NS) DOU VIDENSEF F CAPAC COR VFD UTLETS ALL COOF ES SHALL OINT LOV DETAILS. E FOR PF STALLAT ATION LIS TH ONE S MINIMUM /H Z | 4 4 <td>49.4 44.7 27.1 27.1 36.3 36.3 RAP, EXV, TOTAL STRUCTION WITH IRE GRILLES, 304 ATE LEAVING AIF FAN SPEED TO M SEE MECHA SION AND INSTAL RFORMANCE PEN EDULED IEER BAS FACE WITH DDC. INB TO STRUCTUR NEERED INSTALL/ SHALL BE PERFO PROVIDED ACCUF ANIZED FILTER FF 7 SALT SPRAY R/ Image: Comparison of the structure STEPS Image: Comparison of the struct</td> <td>60 35 45 AT MANUFAC ATION OF SEN ATION DRAWING RE. EQUIPMEN TION DRAWING ATELY. AMES WITH ME TING. AT MANUFAC Titu Ti</td> <td>208-3-60 208-3-</td> <td>100 100 100 100 100 100 000000000000000000000000000000000000</td> <td>11 5 8 ASINGS A SS DOOR: NIZED FIL T STATIC IV. 26 TO IV. 26 TO CTORS. E CAPACI JRER IS R MODEL STED ABC 08 08 12 08 08 12 08 12 08 12 14 12 14 12 14 12 14 12 14 12 14 12 14 12 14 12 14 12 14 12 14 12 14 12 14 12 14 12 14</td> <td>13.7 16.5 16.1 10.1</td> <td>95. 50. 72. EZE-STAT AMES, E-CO URE SENSO E WIRING / HRI CONDI SIBLE FOR SITE AND 14 FILTERS</td> <td>8 8 8 5 OPTIONS. OATED CON OR BY RTU AND POWE TIONS. PROVIDING STAMPED A S. ADD 0.75</td> <td>75.0/63. 75.0/63. 75.0/63. NDENSER MFR. COOR FOR THE SENGINE NO SEAL PRESSU MAR ACCU NOTE 1. 2. 3. 4. 5. 6. 7. 8.</td> <td></td> | 49.4 44.7 27.1 27.1 36.3 36.3 RAP, EXV, TOTAL STRUCTION WITH IRE GRILLES, 304 ATE LEAVING AIF FAN SPEED TO M SEE MECHA SION AND INSTAL RFORMANCE PEN EDULED IEER BAS FACE WITH DDC. INB TO STRUCTUR NEERED INSTALL/ SHALL BE PERFO PROVIDED ACCUF ANIZED FILTER FF 7 SALT SPRAY R/ Image: Comparison of the structure STEPS Image: Comparison of the struct | 60 35 45 AT MANUFAC ATION OF SEN ATION DRAWING RE. EQUIPMEN TION DRAWING ATELY. AMES WITH ME TING. AT MANUFAC Titu Ti | 208-3-60 208-3- | 100 100 100 100 100 100 000000000000000000000000000000000000 | 11 5 8 ASINGS A SS DOOR: NIZED FIL T STATIC IV. 26 TO IV. 26 TO CTORS. E CAPACI JRER IS R MODEL STED ABC 08 08 12 08 08 12 08 12 08 12 14 12 14 12 14 12 14 12 14 12 14 12 14 12 14 12 14 12 14 12 14 12 14 12 14 12 14 12 14 | 13.7 16.5 16.1 10.1 | 95. 50. 72. EZE-STAT AMES, E-CO URE SENSO E WIRING / HRI CONDI SIBLE FOR SITE AND 14 FILTERS | 8 8 8 5 OPTIONS. OATED CON OR BY RTU AND POWE TIONS. PROVIDING STAMPED A S. ADD 0.75 | 75.0/63. 75.0/63. 75.0/63. NDENSER MFR. COOR FOR THE SENGINE NO SEAL PRESSU MAR ACCU NOTE 1. 2. 3. 4. 5. 6. 7. 8. | |

4. FURNISH VAV BOXES LESS THAN 24" DEEP.

FURNISH WITH SLIP AND DRIVE CONNECTIONS.

6. PROVIDE SOUND ATTENUATOR INTEGRAL TO ELECTRIC HEATING COIL SECTION.

MINIMUM AIR FLOW SHALL BE 50% DURING HEATING MODE. 7.

8. PROVIDE TITUS 1" ECO SHIELD WITH FOIL FACING OR EQUAL.

PROVIDE AEROCROSS INLET AIR VELOCITY SENSOR OR EQUAL.

| | | COND. REHEA | T COIL- DE | EHUMID COND | HEATING | | | | UNIT | | | |
|--------|-------|-------------|------------|-------------|---------|----------|------|----------|---------|--------|--------------|------|
| | | | | | | ELECTRIC | | # COMP./ | EER/ | | MANUFACTURER | |
| TCAP | SCAP | EAT | TCAP | LAT | EAT | TCAP | LAT | STAGES | IEER | WEIGHT | MODEL# | |
| MBH | MBH | (DB/WB) | MBH | (DB/WB) | (DB) | KW | (DB) | | AHRI | LBS | DAIKIN | NOTE |
| | | | | | | | | | | | | |
| 170.70 | 59.90 | 51.0/51.0 | 37.20 | 70.0/58.4 | 40.0 | 18 | 68.0 | 2 / INF | 11/17.7 | 2312 | DPS015A | ALL |
| | | | | | | | | | | | | |
| 170.70 | 59.90 | 51.0/51.0 | 37.20 | 70.0/58.4 | 40.0 | 18 | 68.0 | 2 / INF | 11/17.7 | 2312 | DPS015A | ALL |

IRS WATER IMMERSION RESISTANCE.

ALYSIS OF:

ICENSED ENGINEER.

IERV 14 FILTERS.

| | ł | HEATING | ì | | | | DAIKIN |
|-----------|----|---------|----------|---------------|--------|-------|---------|
| LAT | | | ELECT. | MIN. | WEIGHT | NOTES | MODEL |
| DB/WB | KW | STG. | V-PH-HZ | EER/IEER | LB | | NUMBER |
| 55.6/55.1 | - | - | 208-3-60 | 12.4/19.3 | 2118 | ALL | DPS010A |
| 54.3/54.2 | - | - | 208-3-60 | 12.5/20.6 | 1968 | ALL | DPS007A |
| 54.1/53.8 | - | - | 208-3-60 | 12.4/19.3 | 2118 | ALL | DPS010A |
| 54.9/54.7 | - | - | 208-3-60 | 13/ 18.5 SEER | 1281 | ALL | DPS005A |
| 53.6/53.5 | - | - | 208-3-60 | 11.9/19.8 | 1868 | ALL | DPS007A |

NSTALLATION WITH DDC.

6. COORDINATE WITH ELECTRICAL CONTRACTOR.

| | \sum | | | \mathcal{A} | | $\$ | ADD.#4 | |
|------------------------|--------|-------|--|---------------|--------------|------------|--------------|-----|
| IL ANALYSIS OF: | | LOUVE | R SCHEDULE | | | | | |
| | \leq | | | CFM | FACE | MIN. FREE | RUSKIN | |
| | 4 | MARK | SERVES | RANGE | SIZE (W X H) | AREA (FT2) | MODEL NUMBER | NOT |
| |) | L-1 | EF-1, EF-2, EF-3, EF-4, EF5, EF-6, EF-7 | 1125 | 36 X 24 | 2.37 | EME520MD | AL |
| XAS LICENSED ENGINEER. | | L-2 | EF-8, EF-9, EF-11, EF-12 | 500 | 36 X 18 | 1.63 | EME520MD | ALI |
| | | L-3 | EF-10, EF-13, EF-14, EF-15, EF-16, EF-17 | 550 | 36 X 18 | 1.63 | EME520MD | ALI |
| OR MERV 14 FILTERS. | < | | | | | | | |

OR MERV 14 F NOTES

PRIOR TO ORDERING, COORDINATE LOUVER FINISH AND EXACT FACE SIZE WITH ARCHITECT. PROVIDE STAINLESS STEEL BIRD SCREEN AND HARDWARE. PROVIDE FACTORY APPLIED KYNAR 500 FINISH. 4. PROVIDE WITH TDI PRODUCT EVALUATION REPORT.

IT AIR COOLED CONDENSING UNIT SCHEDULE

| | TOTAL | COND | ELECTRIC | SEER | COMPR | | | WEGHT | | MANUFACTURE |
|---------|--------|------|----------|----------------|--------|-----|------|-------|-------|--------------|
| SERVING | BTU/H | DB | V-PH-HZ | ARI CONDITIONS | STAGES | MCA | MOCP | (LBS) | NOTES | MODEL NUMBER |
| | | | | | | | | | | DAIKIN |
| WAC-1 | 18,000 | 100 | 208-1-60 | 18 | VAR | 15 | 20 | 93 | ALL | RKN18KEVJU |
| | | | | | | | | | | |

ANUFACTURER AND MODEL NUMBER LISTED ARE "OR APPROVED EQUAL". SEE SPECIFICATIONS FOR APPROVED MANUFACTURERS. AND SUBSTITUTION PROCEDURES. NSULATE REFRIGERANT LINES AS PER SPECIFICATIONS. PROVIDE ALUMINUM METAL JACKETING AROUND INSULATION FOR ALL

EXTERIOR EXPOSED LINES.

ER SHALL EXCEED IECC MINIMUM EFFICIENCY AT ARI CONDITIONS.

PROVIDE EVAPORATOR DEFROST CONTROLLER FOR MINIMUM CIRCUIT. BIGHT GLASSES, FILTER DRYERS, AND FIELD SUPPLIED EXPANSION VALVES ARE NOT TO BE USED ON DAIKIN EQUIPMENT.

PROVIDE INVERTER DRIVEN COMPRESSOR FOR IMPROVED HUMIDITY CONTROL. SAFETY DISCONNECT TO BE PROVIDED BY DIV. 26. ELECTRICAL CONTRACTOR TO PROVIDE SINGLE CIRCUIT POWER FROM SERVICE TO OUTDOOR UNIT AND WIRE TO INDOOR UNIT.

PROVIDE ATTACHMENT OF ACCU TO ROOF STRUCTURE CAPABLE OF WITHSTANDING THE LOCAL WIND PRESSURES AS PER IBC. PROVIDE CALCULATIONS AND ATTACHMENT INSTALLATION INSTRUCTIONS SEALED BY A LICENSED ENGINEER. REFER TO SPECIFICATIONS FOR MORE INFORMATION ON THIS DELEGATED DESIGN.

IT WALL MOUNT EVAPORATOR SCHEDULE

| | | TOTAL | | | | | | COOLING | 3 | | | |
|-----|----------|-----------|-------|-----|------|----------|-------|---------|-------|-------|-------|----------------|
| IED | | CFM | ESP | | | ELECT. | TOTAL | EAT | LAT | WT | NOTES | MANUFACTURER & |
| | LOCATION | MIN./MAX. | IN WG | MCA | MOCP | V-P-H | BTU/H | DB/WB | DB/WB | (LBS) | | MODEL NUMBER |
| | | | | | | | | | | | | DAIKIN |
| J-1 | SEE PLAN | 403/572 | 0.10 | - | - | 208-1-60 | 18000 | 80/67 | 55/55 | 26.5 | ALL | FTXN18KVJU |

ACTURER AND MODEL NUMBER LISTED ARE "OR APPROVED EQUAL". SEE SPECIFICATIONS FOR APPROVED MANUFACTURERS.

AND SUBSTITUTION PROCEDURES. FILTER SECTION SHALL BE WIRE FRAMED SECTION.

PROVIDE MOUNTING BRACKET

2.

3.

4.

5.

6.

PROVIDE WALL MOUNTED AND WIRED 7-DAY PROGRAMMABLE T-STAT IN LIEU OF WIRELESS REMOTE.

ELECTRICAL CONTRACTOR TO PROVIDE SINGLE CIRCUIT POWER FROM SERVICE TO OUTDOOR UNIT AND WIRE TO INDOOR UNIT. PROVIDE FACTORY SUPPLIED CONDENSATE PUMP.

| MARK | ROOM SERVING | Specific Prod Descriptior | uct EL |
|---------------|--------------------------------------|-------------------------------|--------------------|
| EF-1 | PATIENT RR | Ceiling Exha | ust 115 |
| EF-2 | STAFF RR | Fan Ceiling Exhai | ust 115 |
| EF-3 | CUSTODIAN | Fan Ceiling Exhau | ust 115 |
| EF-4 | STORAGE | Fan Ceiling Exhai | ust 115 |
| EF-5 | SHARED | Fan Ceiling Exhau | ust 115 |
| EF-6 | PROCEDURE | Fan Ceiling Exha | ust 115 |
| EF-7 | PROCEDURE SOILED UTILITY | Fan Ceiling Exhau | ust 115 |
| EF-8 | STAFF RR | Fan Ceiling Exhai | ust 115 |
| EF-9 | STAFF RR | Fan Ceiling Exhau | ust 115 |
| EF-10 | SHARED LAB | Fan Ceiling Exhau | ust 115 |
| EF-11 | MEN'S RR | Fan Ceiling Exhau | ust 115 |
| EF-12 | WOMEN'S RR | Fan Ceiling Exhai | ust 115 |
| EF-13 | SHARED | Fan Ceiling Exhai | ust 115 |
| EF-14 | INJECTION PATIENT RR | Fan Ceiling Exhai | ust 115 |
| EF-15 | CUSTODIAN | Fan Ceiling Exhai | ust 115 |
| EF-16 | PATIENT RR | Fan Ceiling Exhai | ust 115 |
| EF-17 | STAFF RR | Fan Ceiling Exhai | ust 115 |
| | | Fan | |
| NOTES 1. | PROVIDE FACTORY | MOUNTED DIS | |
| 2. | | ND MODEL NUM | |
| 3. 4. | PROVIDE FAN WITH | ALL ALUMINUN | M BACKDF |
| 5. 6. | PROVIDE DELUXE A PROVIDE SPRING T | LUMINUM GRIL (PE VIBRATION | .LE. NISOLATO |
| ONTROL NOTES: | | | |
| A. | PROVIDE DDC STAR | I/STOP POINT | S. REFER |
| | AIR DEV | ICE & D | IFFU |
| | | | |
| | SUPPLY AIR | DIFFUSE | (SD-1) T |
| | | | |
| | CLG. MOI | DULE | |
| | INCHE | S | |
| | 24 X 2 | 24 | |
| | SUPPLY AIR | GRILLE (S | D-2) SI |
| | | | |
| | NOMINAL DI | ICT SIZE | |
| | INCHE | S | |
| | | 1) | |
| NOTES | 18 X | 6 | |
| ALL | SUPPLY AIR | DIFFUSEF | ₹ (SD-3) |
| ALL | CEM | | |
| | RANG | E | |
| | 0-350 |) | |
| | SUPPLY AIR | DIFFUSEF | R (SD-4) |
| | | | |
| | CFM RANG | E | |
| | 0-200 |) | |
| | RETURN AN | D TRANSF | |
| | | | |
| | CFM | | |
| | RANG | Έ | |
| | 0 - 160 | 00 | |
| | | | २८- ७) |
| | | · •······ (I | |
| | CFM | | (|
| | RANG | E | |
| | 0 - 40 | 0 | |
| | NOTES: | | |
| | 1. 2. | | PROVIDE PROVIDE |
| | 3. | | |
| | 4. 5. | | PROVIDE |
| | 6. | | AIR DEVI |

| | / | | | | | | | | | | | |
|---|-------|---------------------|---------------------------------|---------------------|--------------------------|-------------|---------------------------------|-------------|-----------------------------|-------------|-------|------------------|
| 2 | EXHA | UST F | AN SC | HEDU | JLE | | | | | | | |
| / | MARK | ROOM SERVING | Specific Product Description | ELECTRICAL V/P/H | Config Total Air Flow | Motor Power | Config Total Static Pressure | Inlet Sones | MANUFACTURER & MODEL NUMBER | Unit Weight | Notes | CONTROL NOTES |
| | EF-1 | PATIENT RR | Ceiling Exhaust Fan | 115 V / 1 / 60 Hz | 75 CFM | 128 W | 0.40 in-wg | 2 | Greenheck SP-B150 | 19 | ALL | A |
| | EF-2 | STAFF RR | Ceiling Exhaust Fan | 115 V / 1 / 60 Hz | 75 CFM | 128 W | 0.40 in-wg | 2 | Greenheck SP-B150 | 19 | ALL | A |
| | EF-3 | CUSTODIAN | Ceiling Exhaust Fan | 115 V / 1 / 60 Hz | 75 CFM | 128 W | 0.40 in-wg | 2 | Greenheck SP-B150 | 19 | ALL | A |
| | EF-4 | STORAGE | Ceiling Exhaust Fan | 115 V / 1 / 60 Hz | 50 CFM | 128 W | 0.40 in-wg | 2 | Greenheck SP-B150 | 19 | ALL | A |
| | EF-5 | SHARED PROCEDURE | Ceiling Exhaust Fan | 115 V / 1 / 60 Hz | 375 CFM | 350 W | 0.40 in-wg | 3 | Greenheck SP-A700 | 36 | ALL | A |
|) | EF-6 | SHARED PROCEDURE | Ceiling Exhaust Fan | 115 V / 1 / 60 Hz | 375 CFM | 350 W | 0.40 in-wg | 3 | Greenheck SP-A700 | 36 | ALL | A |
| | EF-7 | SOILED UTILITY | Ceiling Exhaust Fan | 115 V / 1 / 60 Hz | 100 CFM | 128 W | 0.40 in-wg | 2 | Greenheck SP-B150 | 19 | ALL | A |
|) | EF-8 | STAFF RR | Ceiling Exhaust Fan | 115 V / 1 / 60 Hz | 75 CFM | 128 W | 0.40 in-wg | 2 | Greenheck SP-B150 | 19 | ALL | A |
| | EF-9 | STAFF RR | Ceiling Exhaust Fan | 115 V / 1 / 60 Hz | 75 CFM | 128 W | 0.40 in-wg | 2 | Greenheck SP-B150 | 19 | ALL | A |
|) | EF-10 | SHARED LAB | Ceiling Exhaust Fan | 115 V / 1 / 60 Hz | 100 CFM | 128 W | 0.40 in-wg | 2 | Greenheck SP-B150 | 19 | ALL | A |
| | EF-11 | MEN'S RR | Ceiling Exhaust Fan | 115 V / 1 / 60 Hz | 175 CFM | 135 W | 0.40 in-wg | 3 | Greenheck SP-A700 | 33 | ALL | A |
|) | EF-12 | WOMEN'S RR | Ceiling Exhaust Fan | 115 V / 1 / 60 Hz | 175 CFM | 135 W | 0.40 in-wg | 3 | Greenheck SP-A700 | 33 | ALL | A |
| | EF-13 | SHARED INJECTION | Ceiling Exhaust Fan | 115 V / 1 / 60 Hz | 150 CFM | 135 W | 0.40 in-wg | 3 | Greenheck SP-A390 | 33 | ALL | A |
| | EF-14 | PATIENT RR | Ceiling Exhaust Fan | 115 V / 1 / 60 Hz | 75 CFM | 128 W | 0.40 in-wg | 2 | Greenheck SP-B150 | 19 | ALL | A |
| | EF-15 | CUSTODIAN | Ceiling Exhaust Fan | 115 V / 1 / 60 Hz | 75 CFM | 128 W | 0.40 in-wg | 2 | Greenheck SP-B150 | 19 | ALL | A |
| | EF-16 | PATIENT RR | Ceiling Exhaust Fan | 115 V / 1 / 60 Hz | 75 CFM | 128 W | 0.40 in-wg | 2 | Greenheck SP-B150 | 19 | ALL | A |
| / | EF-17 | STAFF RR | Ceiling Exhaust Fan | 115 V / 1 / 60 Hz | 75 CFM | 128 W | 0.40 in-wg | 2 | Greenheck SP-B150 | 19 | ALL | A |

STED ARE "OR APPROVED EQUAL." REFER TO SPECIFICATIONS.

ONTROLLER. COORDINATE INSTALLATION WITH ELECTRICAL CONTRACTOR. DRAFT DAMPER.

TORS FROM MANUFACTURER.

R TO SEQUENCES OF OPERATIONS.

USER SCHEDULE

| TITUS OMNI-AA | | DESCRIPTION: ALUMINUM SQUARE CEILI | NG DIFFUSER, | |
|------------------|-------------------------|-------------------------------------|---|---------------|
| NC < 20 | | BORDER TYPE 3, COLOR WHITE WITH RC | OUND NECK AND | |
| | | FULL FACE | DISCUSSO | |
| FACE | ROUND NECK | FLEX | DIFFUSER | NOTEO |
| SIZE | SIZE | DUCI | DIFFUSION | NOTES |
| INCHES | | SIZE | PATTERN & CFM | |
| 24 X 24 | TO MATCH NC CRITERIA | SEE PLAN | SD1-CFM | 1-4,6 |
| IDE WALL | | | | |
| TITUS 301FL | | DESCRIPTION: AEROBLADE, ALUMINUM, | DOUBLE DEFLECTION DIFFUS | ER |
| NC < 20 | | BORDER TYPE 1 (SURFACE MOUNT) | | |
| | | STATIC PRESSURE: < 0.05" W.G. | | |
| | FACE SIZE | | DIFFUSER | |
| | INCHES | | DIFFUSION | NOTES |
| | (INCLUDING FRAME) | | PATTERN & CFM | |
| | (| | | |
| | INLET SIZE PLUS 1-3/4" | | SD2-CFM | 1-4,6,8 |
|) SIDE WALL | | | | |
| , TITUS ML-39 | | DESCRIPTION: HIGH PERFORMANCE, LIN | EAR SLOT | |
| NC < 17 | | DIFFUSER, SEE PLAN FOR LENGTH. | | |
| | SIZE | (ACTIVE SECTION) | DIFFUSER | |
| | | | DIFFUSION | NOTES |
| # 01010 | INCHES | INCHES | PATTERN & CEM | NOTEO |
| 2 | 1 | 48" | SD3-CEM | 14670 |
| | I | то | 000-01 W | 1, 4, 0, 7, 5 |
|) SIDE WALL | | | | |
| TITUS ML-39 | | DESCRIPTION: HIGH PERFORMANCE, LIN | EAR SLOT | |
| NC < 17 | | DIFFUSER. SEE PLAN FOR LENGTH. | | |
| | SIZE | (ACTIVE SECTION) | DIFFUSER | |
| # SLOTS | OF SLOTS | PLENUM LENGTH | DIFFUSION | NOTES |
| | INCHES | INCHES | PATTERN & CFM | |
| 2 | 1 | 36" | SD4-CFM | 1, 4, 6, 7, 9 |
| R GRILLE (RG-1] | | | | |
| | | DESCRIPTION: ALLIMINUM GRID EGGCRA | TE RETURN GRILLE WITH | |
| NC < 20 | | BORDER TYPE 3 (LAY-IN) OR BORDER TY | P 1 (SURFACE MOUNT) | |
| | | DIFFUSER | | |
| | | | | NOTES |
| | | | | NULES |
| | (INLE1) | | | 4 4 0 |
| 24 X 24 | 10 X 10 | | | 1,4,0 |
| 24 / 24 | 10 \ 10 | | J | 1,4,0 |
| TITUS 50F | | DESCRIPTION: ALUMINUM GRID EGGCRA | | |
| NC < 20 | | BORDER TYPE 3 (LAY-IN) OR BORDER TY | P 1 (SURFACE MOUNT). | |
| CLG. MODULE | NOMINAL DUCT SIZE | DIFFUSER | (- · · · · · · · · · · · · · · · · · · | |
| SIZE | INCHES | DIFFUSION | | NOTES |
| INCHES | | PATTERN & CEM | | NOTES |
| | 20 X 8 | RG2-CEM (RETURN AIR GRILLES ONLY) | | 146 |
| 24 X 12 | 6 Y 1 G 1 J | THE OTHER OTHER OTHER OTHER | | 1,7,0 |
| 24 X 12 | 2070 | | | |
| 24 X 12 | 20,00 | | | |

DE MOUNTING FRAME TYPE COMPATIBLE WITH SCHEDULED CEILING OR WALL (SURFACE OR LAY-IN).

DE BALANCING DAMPER ON ALL EXHAUST GRILLES. VICES SHALL MATCH ARCHITECTURAL FINISH. COORDINATE COLOR WITH ARCHITECT.

PROVIDE BORDER TYPE 15, WITH CONCEALED FASTENING.

PROVIDE NECK MOUNTED OPPOSED BLADE DAMPER. PROVIDE BORDER TYPE 9A, WITH FLANGE BORDER.



119 W. VAN BUREN AVE. STE. 101 PHONE: 956-230-3435 TEXAS REGISTERED ENGINEERING FIRM F-15998

| Project # 18v15 Project # 18v15 Owner Owner UTRGV - SCHOOL OF MEDICINE - JACKSON RD. Enter address here Machiners | Project # 18/15 Project # 18/15 Project # 18/15 Project # 18/15 Owner Owner UTRGV - SCHOOL OF MEDICINE - JACKSON RD. Enter address here Enter address here Mechanical Rest in Process in Proces |
|---|---|
| Project # 18v15 Project # 18v15 Owner UTRGV - SCHOOL OF MEDICINE - JACKSON RD. Enter address here | Project # 18v15 Project # 18v15 Owner UTRGV - SCHOOL OF MEDICINE - JACKSON RD. Enter address here Mechanical Mechanical |
| | Mechanical |

M5.01